



**Atacama  
Large  
Millimeter  
Array**

# SDM Tables Short Description

COMP-70.75.00.00-00?-A-DSN

February 24, 2011

*Design Document*

F.Viallefond, R. Lucas



# SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 2

## Contents

<b>1</b>	<b>List of ASDM Tables</b>	<b>5</b>
1.1	Versioning information for the <b>SDM</b> .	6
1.2	Main Table	7
1.3	AlmaRadiometer Table	9
1.4	Annotation Table	10
1.5	Antenna Table	12
1.6	<b>*DELETE* Beam Table *DELETE*</b>	14
1.7	CalAmpli Table	15
1.8	CalAtmosphere Table	17
1.9	CalBandpass Table	20
1.10	CalCurve Table	22
1.11	CalData Table	24
1.12	CalDelay Table	26
1.13	CalDevice Table	28
1.14	CalFlux Table	30
1.15	CalFocus Table	32
1.16	CalFocusModel Table	35
1.17	CalGain Table	37
1.18	CalHolography Table	38
1.19	CalPhase Table	41
1.20	CalPointing Table	43
1.21	CalPointingModel Table	46
1.22	CalPosition Table	48
1.23	CalPrimaryBeam Table	50
1.24	CalReduction Table	52
1.25	CalSeeing Table	54
1.26	CalWVR Table	56
1.27	ConfigDescription Table	59
1.28	CorrelatorMode Table	61
1.29	DataDescription Table	62
1.30	DelayModel Table	63
1.31	Doppler Table	64
1.32	Ephemeris Table	65
1.33	ExecBlock Table	66
1.34	Feed Table	69
1.35	Field Table	71
1.36	Flag Table	73
1.37	Focus Table	75
1.38	FocusModel Table	76
1.39	FreqOffset Table	77
1.40	GainTracking Table	78
1.41	Holography Table	80
1.42	Pointing Table	81



# SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 3

1.43	PointingModel Table . . . . .	83
1.44	Polarization Table . . . . .	84
1.45	Processor Table . . . . .	85
1.46	Receiver Table . . . . .	86
1.47	SBSummary Table . . . . .	87
1.48	<b>*NNEW* Scale Table *NEW*</b> . . . . .	89
1.49	Scan Table . . . . .	90
1.50	Source Table . . . . .	92
1.51	SpectralWindow Table . . . . .	95
1.52	SquareLawDetector Table . . . . .	98
1.53	State Table . . . . .	99
1.54	Station Table . . . . .	100
1.55	Subscan Table . . . . .	101
1.56	SwitchCycle Table . . . . .	102
1.57	SysCal Table . . . . .	103
1.58	SysPower Table . . . . .	105
1.59	WVMCal Table . . . . .	106
1.60	Weather Table . . . . .	107

## 2 List of Enumerations 109

2.1	Versioning information for the enumerations. . . . .	110
2.2	ACAPolarization . . . . .	111
2.3	AccumMode . . . . .	111
2.4	AntennaMake . . . . .	111
2.5	AntennaMotionPattern . . . . .	111
2.6	AntennaType . . . . .	112
2.7	AssociatedCalNature . . . . .	112
2.8	AssociatedFieldNature . . . . .	112
2.9	AtmPhaseCorrection . . . . .	112
2.10	AxisName . . . . .	112
2.11	BasebandName . . . . .	113
2.12	BaselineReferenceCode . . . . .	113
2.13	CalCurveType . . . . .	114
2.14	CalDataOrigin . . . . .	114
2.15	CalType . . . . .	115
2.16	CalibrationDevice . . . . .	115
2.17	CalibrationFunction . . . . .	116
2.18	CalibrationMode . . . . .	116
2.19	CalibrationSet . . . . .	116
2.20	CorrelationBit . . . . .	116
2.21	CorrelationMode . . . . .	117
2.22	CorrelatorCalibration . . . . .	117
2.23	CorrelatorName . . . . .	117
2.24	CorrelatorType . . . . .	117
2.25	DataContent . . . . .	118



# SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 4

2.26	<b>DataScale</b>	118
2.27	DetectorBandType	118
2.28	DirectionReferenceCode	118
2.29	DopplerReferenceCode	119
2.30	<b>DopplerTrackingMode</b>	120
2.31	FieldCode	120
2.32	FilterMode	120
2.33	FluxCalibrationMethod	120
2.34	FocusMethod	120
2.35	FrequencyReferenceCode	121
2.36	HolographyChannelType	121
2.37	InvalidatingCondition	121
2.38	NetSideband	121
2.39	PointingMethod	122
2.40	PointingModelMode	122
2.41	PolarizationType	122
2.42	PositionMethod	122
2.43	PositionReferenceCode	122
2.44	PrimitiveDataType	123
2.45	ProcessorSubType	123
2.46	ProcessorType	123
2.47	RadialVelocityReferenceCode	123
2.48	ReceiverBand	124
2.49	ReceiverSideband	125
2.50	SBType	125
2.51	ScanIntent	125
2.52	SchedulerMode	126
2.53	SidebandProcessingMode	126
2.54	SourceModel	126
2.55	SpectralResolutionType	126
2.56	StationType	127
2.57	StokesParameter	127
2.58	SubscanIntent	128
2.59	SwitchingMode	128
2.60	SyscalMethod	129
2.61	TimeSampling	129
2.62	<b>TimeScale</b>	129
2.63	<b>WeightType</b>	129
2.64	WVRMethod	129
2.65	WindowFunction	129



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 5

### 1 List of ASDM Tables

This document is just a container for the list of ASDM Tables. More documentation is envisaged in the final document which will include a general introduction.

Note: The order of keys in this document is NOT alphabetical; the hierarchical order matters and is actually different. In particular it has been changed in the CalDM Tables.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 6

### 1.1 Versioning information for the **SDM**.

- Version : 2
- CVS revision : 1.58
- CVS branch : HEAD



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 7

### 1.2 Main Table

Contains links to all data subsets. Each data subset is contained in a separate entity, usually a BLOB.

Main		
Name	Type (Shape)	Comment
<i>Key</i>		
time	ArrayTime	mid point of scheduled period.
configDescriptionId	Tag	Configuration description identifier.
fieldId	Tag	Field identifier.
<i>Required Data</i>		
numAntenna	int	$N_{Ante}$ Number of antennas.
timeSampling	TimeSampling	time sampling mode.
interval	Interval	data sampling interval.
numIntegration	int	$N_{Inte}$ number of integrations.
scanNumber	int	scan number.
subscanNumber	int	subscan number.
dataSize	long long	size of the binary data , as a number of bytes.
dataUID	EntityId	reference to the binary data.
stateId	Tag [ $N_{Ant}$ ]	State identifier.
execBlockId	Tag	ExecBlock identifier.
<i>Optional Data</i>		
*DELETE* flagRow	bool	row flag.

#### Column Descriptions:

**time** : The mid-point of the scheduled period for the row, thus not taking into account the effects of data blanking and any overhead.

**configDescriptionId** : The Configuration Description Table identifier. Note that two or more sub-arrays cannot refer to the same Configuration Description row. The Configuration Description thus makes possible to identify the various subarrays if more than one have been used in the same data set.

**fieldId** : The Field Identifier used in the Field Table.

**numAntenna** : The number of antennas. Provides the size of **stateId**.

**timeSampling** : This specifies whether the sampling interval is divided into simple integrations, or into integrations further divided into sub-integrations (for channel averaged correlator data).

**interval** : This is the nominal data interval, as scheduled, for the whole row. This means that data taking was scheduled to start a **time-interval/2** and end at **time+interval/2**. **Interval** corresponds to the sum of all integrations and does not include the effects of blanking (bad data) or partial integrations. In ALMA this is the scheduled duration of the subscan. For the actual subscan start and end times see the Subscan Table.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 8

**numIntegration** : The number of integrations in **interval**. For **ALMA** this is either true integrations (for full spectral resolution data), or the total number of subintegrations in **interval** (for channel -averaged spectral data).

**scanNumber** : In **ALMA** a scan is an amount of data taken to reach a single result (e.g. a simple calibration). The scan numbers increment from 1 inside an Execution Block.

**subscanNumber** : In **ALMA** a Subscan is the minimum amount of data taken by executing a single Control Command Language (CCL) command. There can be several data cells for each subscan corresponding to different backends (correlator, total power detectors) or different results of the same backend (channel averaged or full-resolution data from a Correlator). In each scan there is at least one subscan.

**dataSize** : Total size, in bytes, of the binary data file.

**dataUID** : This is a string that specifies the data object.

**stateId** : The State identifier used in the State Table.

**execBlockId** : The ExecBlock identifier used in the ExecBlock Table. For ALMA the ExecBlocks represent each execution of a Scheduling Block.

**\*DELETE\* flagRow** : A boolean which is True if the entire row is flagged. **\*DELETE\***





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 9

### 1.3 AlmaRadiometer Table

Properties of the Radiometer receiver/backend (used to monitor water vapour content and correct phases). Note that standard properties (like spectral coverage) are in the generic tables (like SpectralWindow).

AlmaRadiometer		
Name	Type (Shape)	Comment
<i>Key</i>		
almaRadiometerId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
<i>Optional Data</i>		
numAntenna	int	$N_{Ante}$ the number of antennas.
spectralWindowId	Tag [ $N_{Ant}$ ]	the references to the actual spectral windows (one spectral window per antenna).

#### Column Descriptions:

almaRadiometerId : **ALMA** Radiometer Table identifier.  
 numAntenna : The number of antennas to which the data refer.  
 spectralWindowId : enter tag descr. here



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 10

### 1.4 Annotation Table

The Annotation Table is intended to offer space for unexpected data to be added in the software development process at short notice, without redefining the data model.

Annotation		
Name	Type (Shape)	Comment
<i>Key</i>		
annotationId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
time	ArrayTime	<b>start time</b> of the interval of time on which the recorded information is pertinent.
issue	string	name of this annotation.
details	string	details of this annotation.
<i>Optional Data</i>		
numAntenna	int	$N_{Ante}$ number of antennas.
basebandName	BasebandName [ $N_{BB}$ ]	an array of numBaseband baseband names.
numBaseband	int	$N_{Base}$ number of basebands.
interval	Interval	time interval
dValue	double	scalar data.
vdValue	double	useful to store an array of double values.
vvdValues	double	useful to store an array of array(s) of double values.
llValue	int64_t	useful to record a long long data.
vllValue	int64_t	useful to store an array of array(s) of long long values.
vvllValue	int64_t	useful to store an array of array(s) long long values.
antennaId	Tag [ $N_{Ant}$ ]	refers to a collection of rows in the AntennaTable.

#### Column Descriptions:

annotationId : Annotation Table identifier.

time : The **start time** of the time interval the data in this row are referring to. This is for documentation purposes only.

issue : A short (preferably 1-word) string that identifies the type of annotation.

details : Details of this entry: this should explain the motivation, the dimensionality and contents of the generic columns: dValue, llValue, vdValue, vllValue, vvdValues, vvllValue.

numAntenna : The number of antennas to which the data refer.

basebandName : The basebands that the baseband-based data in this table refer to.

numBaseband : The number of basebands to which the data refer.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 11

**interval** : Time interval during which the recorded information is pertinent.

**dValue** : space for a scalar floating-point number.

**vdValue** : space for a 1-dimensional array of floating-point data; shape must be made explicit in **details**.

**vvdValues** : space for a 2-dimensional array of floating-point data; shape must be made explicit in **details**.

**l1Value** : space for a scalar integer.

**v11Value** : space for a 1-dimensional array of integer data; shape must be made explicit in **details**.

**vv11Value** : space for a 2-dimensional array of integer data; shape must be made explicit in **details**.

**antennaId** : Antenna Table identifier.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 12

### 1.5 Antenna Table

Antenna characteristics.

Antenna		
Name	Type (Shape)	Comment
<i>Key</i>		
<b>antennaId</b>	Tag	identifies a unique row in the table.
<i>Required Data</i>		
<b>name</b>	string	the antenna's name.
<b>antennaMake</b>	AntennaMake	the antenna's make.
<b>antennaType</b>	AntennaType	the antenna's type.
<b>dishDiameter</b>	Length	the diameter of the main reflector.
<b>position</b>	Length [3]	the antenna's position.
<b>offset</b>	Length [3]	the position's offset.
<b>time</b>	ArrayTime	the time of position's measurement.
<b>stationId</b>	Tag	refers to the station where this antenna is located (i.e. one row in the Station table).
<i>Optional Data</i>		
<b>assocAntennaId</b>	Tag	refers to an associate antenna (i.e. one row in the Antenna table).

#### Column Descriptions:

**antennaId** : Identifies the row in the Antenna Table.

**name** : Provides a unique string identification for the antenna hardware. *Examples: DA41, DV01, PM01 for ALMA; EA01, EA02, EA05 for the EVLA.*

**antennaMake** : Identifies the antenna manufacturer. Antennas with same optical design may have subtle differences if built according to different designs.

**antennaType** : Generic antenna type; e.g. radio antennas are either for ground use or space use.

**dishDiameter** : The diameter of the main reflector (or the largest dimension for non-circular apertures).

**position** : The position of the antenna pedestal reference point, relative to the station reference point, measured in the horizon system at the station position. The antenna pedestal reference point is on the elevation axis, nominally at the same height as the station reference point (ground level), so that the antenna position should be always close to zero if the antenna is well positioned on the station. This is the quantity that has to be re-measured whenever the antenna is moved to a new station.

**offset** : The position of the antenna phase reference point in the Yoke, relative to the antenna pedestal reference point. This is an antenna characteristic that should be unchanged when the antenna is moved to a new station.

- The X component is horizontal along the elevation axis and has no effect of the interferometer phase; it can be set arbitrarily to zero.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 13

- The  $Y$  component is horizontal and perpendicular to the elevation axis; it produces an elevation dependent interferometer phase term and has to be accurately calibrated.
- The  $Z$  component is vertical and can be kept equal to the nominal height of the elevation axis above ground for the antenna's mount. Small variations from the nominal value have the same phase effect as the  $Z$  component of `position`, so they can be ignored.

**PositionOffset Reference: YOKE (Origin: `Antenna.position`)** - The YOKE reference system is defined in ALMA-80.05.00.00-009-B-SPE document; not known in Measures (CASA)

- Note - The relevant distance between axes is in the  $y$  coordinate, not  $x$ ...

`time` : Gives the time at which the positions were measured.

`stationId` : refers to the station where this antenna is located (i.e. one row in the Station table).

**\*DELETE\*** `assocAntennaId` : Identifies an associated antenna in the Table. This can refer to the same antenna with a position measured at a different time. **\*DELETE\***



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 14

### 1.6 **\*DELETE\* Beam Table \*DELETE\***

At the present time, this table is not defined. This table would be needed for the observing system to write suitable primary beam maps in all data sets. It is not clear that this table is really needed. Data reduction software may well access available archived beam measurements (e.g. CalBeam tables) for accurate deconvolution.

Beam		
Name	Type (Shape)	Comment
<i>Key</i>		
beamId	Tag	identifies a unique row in the table.
<i>Required Data</i>		

#### Column Descriptions:

beamId : Beam Table identifier.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 15

### 1.7 CalAmpli Table

Amplitude Calibration Result from Telescope Calibration. This calibration checks that observing amplitude calibrators provide reasonable results: From the antenna-based fringe amplitudes rough aperture efficiencies are determined.

CalAmpli		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the antenna's name.
atmPhaseCorrection	AtmPhaseCorrection	qualifies how the atmospheric phase correction has been applied.
receiverBand	ReceiverBand	the name of the receiver band.
basebandName	BasebandName	identifies the baseband
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
numReceptor	int	$N_{Rec}$ the number of receptors.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	the polarizations of the receptors (an array containing one value per receptor).
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
frequencyRange	Frequency [2]	the frequency range over which the result is valid.
apertureEfficiency	float [ $N_{Rec}$ ]	the aperture efficiency without correction.
apertureEfficiencyError	float [ $N_{Rec}$ ]	the aperture efficiency error.
<i>Optional Data</i>		
correctionValidity	bool	the correction validity.

#### Column Descriptions:

antennaName : Refers uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.

atmPhaseCorrection : the atmospheric phase corrections states for which result is given.

receiverBand : The name of the front-end frequency band being used.

basebandName : The name of the 'baseband pair' which is measured. For ALMA a baseband pair is the signal path identified by a second local oscillator and has two polarizations. **BB\_ALL** may be used if all basebands are fitted together.

calDataId : CalData Table identifier.

calReductionId : CalReduction Table identifier.

numReceptor : The number or polarization receptors (one or two) for which the result is given.

polarizationTypes : The polarization types of the receptors being used.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 16

`startValidTime` : The start of the time validity range for the result.

`endValidTime` : The end of the time validity range for the result.

`frequencyRange` : Frequency range over which the result is valid; **Frequency reference: TOP0.**

`apertureEfficiency` : Antenna aperture efficiency with and/or without phase correction.

`apertureEfficiencyError` : Error on aperture efficiency measurement.

`correctionValidity` : Deduced validity of atmospheric path length correction (from Water Vapour Radiometers).





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 17

### 1.8 CalAtmosphere Table

Results of atmosphere calibration by TelCal. This calibration determines the system temperatures corrected for atmospheric absorption. Ionospheric effects are not dealt with in the Table.

CalAtmosphere		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
receiverBand	ReceiverBand	identifies the receiver band.
basebandName	BasebandName	identifies the baseband
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
numFreq	int	$N_{Freq}$ the number of frequency points.
numLoad	int	$N_{Load}$ the number of loads.
numReceptor	int	$N_{Rece}$ the number of receptors.
forwardEffSpectrum	float [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the spectra of forward efficiencies (one value per receptor, per frequency).
frequencyRange	Frequency [2]	the frequency range.
groundPressure	Pressure	the ground pressure.
groundRelHumidity	Humidity	the ground relative humidity.
frequencySpectrum	Frequency [ $N_{Freq}$ ]	the frequencies.
groundTemperature	Temperature	the ground temperature.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	the polarizations of the receptors (an array with one value per receptor).
powerSkySpectrum	float [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the powers on the sky (one value per receptor per frequency).
powerLoadSpectrum	float [ $N_{Load}$ ] [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the powers on the loads (one value per load per receptor per frequency).
syscalType	SyscalMethod	the type of calibration used.
tAtmSpectrum	Temperature [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the spectra of atmosphere physical temperatures (one value per receptor per frequency).
tRecSpectrum	Temperature [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the spectra of the receptors temperatures (one value per receptor per frequency).
tSysSpectrum	Temperature [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the spectra of system temperatures (one value per receptor per frequency).
tauSpectrum	float [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the spectra of atmospheric optical depths (one value per receptor per frequency).
tAtm	Temperature [ $N_{Rec}$ ]	the atmosphere physical temperatures (one value per receptor).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 18

CalAtmosphere – continued from previous page		
Name	Type (Shape)	Comment
tRec	Temperature [ $N_{Rec}$ ]	the receptors temperatures (one value per receptor).
tSys	Temperature [ $N_{Rec}$ ]	the system temperatures (one value per receptor).
tau	float [ $N_{Rec}$ ]	the atmospheric optical depths (one value per receptor).
water	Length [ $N_{Rec}$ ]	the water vapor path lengths (one value per receptor).
waterError	Length [ $N_{Rec}$ ]	the uncertainties of water vapor contents (one value per receptor).
<i>Optional Data</i>		
alphaSpectrum	float [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the alpha coefficients, two loads only (one value per receptor per frequency).
forwardEfficiency	float [ $N_{Rec}$ ]	the forward efficiencies (one value per receptor).
forwardEfficiencyError	double [ $N_{Rec}$ ]	the uncertainties on forwardEfficiency (one value per receptor).
sbGain	float [ $N_{Rec}$ ]	the relative gains of LO1 sideband (one value per receptor).
sbGainError	float [ $N_{Rec}$ ]	the uncertainties on the relative gains of LO1 sideband (one value per receptor).
sbGainSpectrum	float [ $N_{Rec}$ ] [ $N_{Freq}$ ]	the spectra of relative sideband gains (one value per receptor per frequency).

### Column Descriptions:

antennaName : Refers uniquely to the hardware antenna object, as present in the original SDM Antenna table.

receiverBand : The name of the front-end frequency band being used.

basebandName : The name of the 'baseband pair' which is measured. For ALMA a baseband pair is the signal path identified by a second local oscillator and has two polarizations. BB\_ALL may be used if all basebands are fitted together.

calDataId : CalData Table identifier.

calReductionId : CalReduction Table identifier.

startValidTime : The start of the time validity range for the result.

endValidTime : The end of the time validity range for the result.

numFreq : Number of frequency points for which the results are given.

numLoad :  $N_{Load}$  Number of loads used in calibration.

numReceptor : The number or polarization receptors (one or two) for which the result is given.

forwardEffSpectrum : The value of the forward efficiency for each frequency point.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 19

**frequencyRange** : Frequency range over which the result is valid **Frequency reference: TOPO**

**groundPressure** : The atmospheric pressure at the altitude of the observatory.

**groundRelHumidity** : The relative atmospheric humidity (%) at the altitude of the observatory.

**frequencySpectrum** : The frequency values for which the results are given.

**groundTemperature** : The ambient temperature at the observatory.

**polarizationTypes** : The polarization types of the receptors being used.

**powerSkySpectrum** : Observed power on sky.

**powerLoadSpectrum** : Observed power on loads.

**syscalType** : The type of calibration used: a single-direction measurement, or a series of measurements at different elevations ('SkyDip')

**tAtmSpectrum** : The value of atmosphere physical temperature for each frequency point.

**tRecSpectrum** : The value of the receiver temperature for each frequency point.

**tSysSpectrum** : The value of the system temperature for each frequency point.

**tauSpectrum** : The value of the optical depth for each frequency point.

**tAtm** : The physical temperature of the atmosphere absorbing layers.

**tRec** : The receiver noise temperature (the reference plane is at the level where the calibration loads are inserted in the signal path).

**tSys** : The system temperature (corrected for atmospheric absorption and antenna losses).

**tau** : The optical depth of the atmosphere along the line of sight.

**water** : The amount of precipitable water vapour in the atmosphere.

**waterError** : The uncertainty of the amount of precipitable water vapour in the atmosphere.

**alphaSpectrum** : alpha coefficient (two-load only); see *Amplitude Calibration steps* memo.

**forwardEfficiency** : This is the coupling factor to the sky, that is the fraction of the antenna beam that sees the emission from the atmosphere.

**forwardEfficiencyError** : The uncertainty of **forwardEfficiency**

**sbGain** : The relative gain of the side band. This is the ratio of the gain in the first LO sideband used to obtain the **frequencyRange** relative to the total (dual-sideband) gain.

**sbGainError** : Uncertainty on **sbGain**.

**sbGainSpectrum** : The value of the relative side band gain for each spectral point. Optional for EVLA, mandatory for ALMA.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 20

### 1.9 CalBandpass Table

Result of passband calibration performed on-line by TelCal.

CalBandpass		
Name	Type (Shape)	Comment
<i>Key</i>		
basebandName	BasebandName	identifies the baseband.
sideband	NetSideband	identifies the first LO sideband.
atmPhaseCorrection	AtmPhaseCorrection	qualifies how the atmospheric phase correction has been applied.
typeCurve	CalCurveType	identifies the type of curve.
receiverBand	ReceiverBand	identifies the receiver band.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
numAntenna	int	$N_{Ante}$ the number of antennas.
numPoly	int	$N_{Poly}$ the number of coefficients of the polynomial.
numReceptor	int	$N_{Recc}$ the number of receptors.
antennaNames	string [ $N_{Ant}$ ]	the names of the antennas.
refAntennaName	string	the name of the reference antenna.
freqLimits	Frequency [2]	the frequency range for the polynomial description of the passband.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	the polarizations of the receptors (one value per receptor).
curve	float [ $N_{Ant}$ ] [ $N_{Rec}$ ] [ $N_{Poly}$ ]	the amplitude or phase coefficients, depending on the value of typeCurve (one array of numPoly values per antenna per receptor).
reducedChiSquared	double [ $N_{Rec}$ ]	measures the quality of the least squares fits (one value per receptor).
<i>Optional Data</i>		
numBaseline	int	$N_{Base}$ the number of baselines.
rms	float [ $N_{Rec}$ ] [ $N_{BL}$ ]	the amplitude or phase residuals ( one array of numBaseline values per receptor).

#### Column Descriptions:

basebandName : The name of the 'baseband pair' which is measured. For ALMA a baseband pair is the signal path identified by a second local oscillator and has two polarizations. BB\_ALL may be used if all basebands



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 21

are fitted together.

**sideband** : First LO Sideband: For sideband-separated spectra one must use different bandpasses for each individual sideband.

**atmPhaseCorrection** : the atmospheric phase corrections states for which result is given.

**typeCurve** : Defines the quantity which is fitted: amplitude or phase.

**receiverBand** : The name of the front-end frequency band being used.

**calDataId** : CalData Table identifier.

**calReductionId** : CalReduction Table identifier.

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**numAntenna** : Number of antennas for which the result is valid.

**numPoly** : Number of polynomial coefficients.

**numReceptor** : The number or polarization receptors (one or two) for which the result is given.

**antennaNames** : Refer uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.

**refAntennaName** : The name of the antenna used as reference to get the antenna-based phases.

**freqLimits** : The frequency limits for the polynomial description of the passband. This frequency interval is reduced to the (-1, 1) interval over which the Chebychev polynomials are defined.

**polarizationTypes** : The polarization types of the receptors being used.

**curve** : The amplitude or phase coefficients.

**reducedChiSquared** : Reduced  $\chi^2$  indicating the quality of the least-squares fit. This is a single number for each polarization as the baselines are to be fitted consistently.

**numBaseline** : Number of baselines for which the result is given

**rms** : The rms of the amplitude/phase residuals for each baseline/polarisation.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 22

### 1.10 CalCurve Table

Result of time-dependent calibration performed on-line by TelCal

CalCurve		
Name	Type (Shape)	Comment
<i>Key</i>		
atmPhaseCorrection	AtmPhaseCorrection	qualifies how the atmospheric phase correction has been applied.
typeCurve	CalCurveType	identifies the type of curve.
receiverBand	ReceiverBand	identifies the receiver band.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
frequencyRange	Frequency [2]	the range of frequencies over which the result is valid.
numAntenna	int	$N_{Ante}$ the number of antennas.
numPoly	int	$N_{Poly}$ the number of coefficients of the polynomials.
numReceptor	int	$N_{Recc}$ the number of receptors.
antennaNames	string [ $N_{Ant}$ ]	the names of the antennas.
refAntennaName	string	the name of the reference antenna.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarizations of the receptors (one value per receptor).
curve	float [ $N_{Ant}$ ] [ $N_{Rec}$ ] [ $N_{Poly}$ ]	the coefficients of the polynomials (one array of numPoly coefficients per receptor per antenna).
reducedChiSquared	double [ $N_{Rec}$ ]	measures the quality of the least squares fits (one value per receptor).
<i>Optional Data</i>		
numBaseline	int	$N_{Base}$ the number of baselines.
rms	float [ $N_{Rec}$ ] [ $N_{BL}$ ]	the amplitude or phase residuals (one array of numBaselines values per receptor).

#### Column Descriptions:

atmPhaseCorrection : the atmospheric phase correction state for which result is given.

typeCurve : Defines the quantity which is fitted: amplitude or phase.

receiverBand : The name of the front-end frequency band being used.

calDataId : CalData Table identifier.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 23

`calReductionId` : CalReduction Table identifier.

`startValidTime` : The start of the time validity range for the result.

`endValidTime` : The end of the time validity range for the result.

`frequencyRange` : Frequency range over which the result is valid. **Frequency reference: TOPO**

`numAntenna` : Number of antennas for which the result is valid.

`numPoly` : The number of coefficients in the Chebichev polynomials used to fit the data.

`numReceptor` : The number or polarization receptors (one or two) for which the result is given.

`antennaNames` : Refer uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.

`refAntennaName` : The name of the antenna used as reference to get the antenna-based phases.

`polarizationTypes` : The polarization types of the receptors being used.

`curve` : These are Chebichev polynomial coefficients. The interval between `startValidTime` and `endValidTime` is reduced to the  $-1,1$  interval over which the Chebychev coefficients are defined. For interferometer amplitude, data is expressed in terms of correlation coefficient; for interferomete phase, coefficients are given in radians.

`reducedChiSquared` : Reduced  $\chi^2$  indicating the quality of the least-squares fit.

`numBaseline` : Number of baselines ffor which the result is given.

`rms` : The root means square deviations of fit residuals.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 24

### 1.11 CalData Table

This table describes the data used to derive the calibration results.

CalData		
Name	Type (Shape)	Comment
<i>Key</i>		
calDataId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
startTimeObserved	ArrayTime	the start time of observation.
endTimeObserved	ArrayTime	the end time of observation.
execBlockUID	EntityId	the UID of the Execution Block.
calDataType	CalDataOrigin	identifies the origin of the data used for the calibration.
calType	CalType	identifies the type of performed calibration.
numScan	int	$N_{Scan}$ the number of scans (in this Execution Block).
scanSet	int [ $N_{Scan}$ ]	the set of scan numbers.
<i>Optional Data</i>		
assocCalDataId	Tag	refers to an associate row in CalDataTable.
assocCalNature	AssociatedCalNature	identifies the nature of the relation with the associate row in CalDataTable.
fieldName	string [ $N_{Scan}$ ]	the names of the fields (one name per scan).
sourceName	string [ $N_{Scan}$ ]	the names of the sources as given during observations (one source name per scan).
sourceCode	string [ $N_{Scan}$ ]	the special characteristics of sources expressed in a textual form (one string per scan).
scanIntent	ScanIntent [ $N_{Scan}$ ]	identifies the intents of the scans (one value per scan).

#### Column Descriptions:

calDataId : Row identifier.

startTimeObserved : The start time of the data set used.

endTimeObserved : The end time of the data set used.

execBlockUID : Archive UID of the ExecBlock.

calDataType : The origin of the data used: Correlator (full resolution or channel averaged data), Total power detectors, WVR receivers, etc. This information is added as e.g. a pointing scan may have been reduced using either total power or interferometry, or the atmosphere may be calibrated using autocorrelations or total power detectors.

calType : This enumerated item tells in which calibration table the results is.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 25

**numScan** : The number of scans in the scan set used.

**scanSet** : The list of scan numbers in the set of scans used.

**assocCalDataId** : This is used to chain data sets obtained in different ExecBlocks, for which scan numbers are re-used.

**assocCalNature** : Nature of the association established by **assocCalDataId**. Normally this is used to refer to data in different execution blocks, for which scan numbers may be re-used.

**fieldName** : The name of the field the array was aimed at.

**sourceName** : Names of the sources as given during observations.

**sourceCode** : Special characteristics of source, e.g. passband calibrator, phase calibrator, flux calibrator.

**scanIntent** : The list of the intents associated with each scan in the data set.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 26

### 1.12 CalDelay Table

Result of delay offset calibration performed on-line by TelCal. This calibration determines the delay offsets to be added in the correlator to compensate for residual cable delays. Delays are entered in seconds but represented as double precision floating point numbers.

CalDelay		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
atmPhaseCorrection	AtmPhaseCorrection	qualifies how the atmospheric phase correction has been applied.
basebandName	BasebandName	Name of the Baseband
receiverBand	ReceiverBand	identifies the receiver band.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of the result validity period.
endValidTime	ArrayTime	the end time of the result validity period.
refAntennaName	string	the name of the reference antenna.
numReceptor	int	$N_{Recc}$ the number of receptors.
delayError	double [ $N_{Rec}$ ]	the uncertainties on the measured delay offsets (one value per receptor).
delayOffset	double [ $N_{Rec}$ ]	the measured delay offsets (one value per receptor).
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarizations of the receptors (one value per receptor).
reducedChiSquared	double [ $N_{Rec}$ ]	measure of the quality of the fit (one value per receptor).
<b>appliedDelay</b>	<b>double [<math>N_{Rec}</math>]</b>	<b>the delay that was applied (one value per receptor).</b>
<i>Optional Data</i>		
crossDelayOffset	double	the measured cross delay offset (reference antenna only).
crossDelayOffsetError	double	the uncertainty for the cross delay offset.
numSideband	int	$N_{Side}$ the number of sideband.
refFreq	Frequency [ $N_{Side}$ ]	the reference frequencies (one value per sideband).
refFreqPhase	Angle [ $N_{Side}$ ]	the phases at reference frequencies (one value per sideband).
sidebands	ReceiverSideband [ $N_{Side}$ ]	identifies the receiver's sidebands (one value per sideband).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 27

### Column Descriptions:

- antennaName** : Refers uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.
- atmPhaseCorrection** : The atmospheric phase corrections states for which result is given.
- basebandName** : The name of the 'baseband pair' which is measured. For ALMA a baseband pair is the signal path identified by a second local oscillator and has two polarizations. **BB\_ALL** may be used if all basebands are fitted together.
- receiverBand** : The name of the front-end frequency band being used.
- calDataId** : CalData Table identifier.
- calReductionId** : CalReduction Table identifier.
- startValidTime** : The start of the time validity range for the result.
- endValidTime** : The end of the time validity range for the result.
- refAntennaName** : The name of the antenna used as reference to get the antenna-based phases.
- numReceptor** : The number or polarization receptors (one or two) for which the result is given.
- delayError** : The statistical uncertainty on the delay offset found by TelCal for the specified antenna, receiver band, and baseband.
- delayOffset** : The delay offset found by TelCal for the specified antenna, receiver band, and baseband.
- polarizationTypes** : The nominal polarization types of the receptors being used.
- reducedChiSquared** : Reduced  $\chi^2$  indicating the quality of the least-squares fit.
- appliedDelay** : the delay that was applied during the observations.
- crossDelayOffset** : The cross-polarization delay offset found by TelCal for the specified receiver band, and baseband . Note : this must be the same for all antennas; this is the delay to be added to Y signals relative to X signals to get a flat frequency dependence of phases for a polarized point source.
- crossDelayOffsetError** : The uncertainty on the cross-polarization delay offset found by TelCal for the specified receiver band, and baseband.
- numSideband** :  $N_{Side}$  Number of Sidebands: in the side-band separated case, data from both sidebands are available for a given baseband. The delay offset should be the same for both sidebands, but the phase in **refFreqPhase** should be sideband-dependent.
- refFreq** : A reference frequency within the band.
- refFreqPhase** : Phase fitted at the frequency **refFreq**.
- sidebands** : Receiver side bands of the reference frequencies given in **refFreq**.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 28

### 1.13 CalDevice Table

Calibration device characteristics. This table is not part of the Calibration Data Model but describes the actual observations; it refers to the amplitude calibration device which includes the hot loads. Calibration device properties are assumed independent of frequency throughout a spectral window.

CalDevice		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable.
spectralWindowId	Tag	refers to a unique row in SpectralWindow Table.
timeInterval	ArrayTimeInterval	the period of validity of the data recorded in this row.
feedId	int	refers to the collection of rows in FeedTable having this value of feedId in their key.
<i>Required Data</i>		
numCalload	int	$N_{Call}$ the number of calibration loads.
calLoadNames	CalibrationDevice [ $N_{Call}$ ]	identifies the calibration loads (an array with one value per load).
<i>Optional Data</i>		
numReceptor	int	$N_{Rece}$ the number of receptors.
calEff	float [ $N_{Rec}$ ] [ $N_{Call}$ ]	the calibration efficiencies (one value per receptor per load).
noiseCal	float [ $N_{Rec}$ ] [ $N_{Call}$ ]	the equivalent temperatures of the of the noise sources used ( <b>two values</b> per load).
coupledNoiseCal	float [ $N_{Rec}$ ] [ $N_{Call}$ ]	<b>doc missing</b>
temperatureLoad	Temperature [ $N_{Call}$ ]	the physical temperatures of the loads for a black body calibration source (one value per load).

#### Column Descriptions:

antennaId : Antenna Table identifier.

spectralWindowId : SpectralWindow Table identifier.

timeInterval : Validity time interval for the data in the row.

feedId : Specifies which feed was used in the Feed Table.

numCalload : The number of calibration loads for which data are given.

calLoadNames : The names of the calibration loads for which data are provided.

numReceptor : The number of receptors.

calEff : The coupling factor of the calibration source to the receiver beam.

noiseCal : The equivalent temperature of the noise source used.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 29

`coupledNoiseCal` : **missing**

`temperatureLoad` : The physical temperature of the load, **in Kelvin** (for a black-body calibration source).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 30

### 1.14 CalFlux Table

Result of flux calibration performed on-line by TelCal. Atmospheric absorption is corrected for. No ionosphere correction has been applied.

CalFlux		
Name	Type (Shape)	Comment
<i>Key</i>		
sourceName	string	the name of the source.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
numFrequencyRanges	int	$N_{Freq}$ the number of frequency ranges.
numStokes	int	$N_{Stok}$ the number of Stokes parameters.
frequencyRanges	Frequency [ $N_{Freq}$ ] [2]	the frequency ranges (one pair of values per range).
fluxMethod	FluxCalibrationMethod	identifies the flux determination method.
flux	double [ $N_{Stok}$ ] [ $N_{Freq}$ ]	the flux densities (one value per Stokes parameter per frequency range).
fluxError	double [ $N_{Stok}$ ] [ $N_{Freq}$ ]	the uncertainties on the flux densities (one value per Stokes parameter per frequency range).
stokes	StokesParameter [ $N_{Stok}$ ]	the Stokes parameter.
<i>Optional Data</i>		
direction	Angle [2]	the direction of the source.
directionCode	DirectionReferenceCode	identifies the reference frame of the source's direction.
directionEquinox	Angle	equinox associated with the reference frame of the source's direction.
PA	Angle [ $N_{Stok}$ ] [ $N_{Freq}$ ]	the position's angles for the source model (one value per Stokes parameter per frequency range).
PAError	Angle [ $N_{Stok}$ ] [ $N_{Freq}$ ]	the uncertainties on the position's angles (one value per Stokes parameter per frequency range).
size	Angle [ $N_{Stok}$ ] [ $N_{Freq}$ ] [2]	the sizes of the source (one pair of angles per Stokes parameter per frequency range).
sizeError	Angle [ $N_{Stok}$ ] [ $N_{Freq}$ ] [2]	the uncertainties of the sizes of the source (one pair of angles per Stokes parameter per frequency range).
sourceModel	SourceModel	identifies the source model.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 31

### Column Descriptions:

**sourceName** : The name of the source for which flux density information was derived.

**calDataId** : CalData Table identifier.

**calReductionId** : CalReductionTable identifier.

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**numFrequencyRanges** : The number of frequency ranges for which flux density information was derived

**numStokes** : The number of Stokes parameters which were measured for this source.

**frequencyRanges** : Frequency ranges over which the result is valid. **Frequency reference: TOPO**

**fluxMethod** : The method which was used to derive flux densities.

**flux** : The derived flux density values.

**fluxError** : The statistical uncertainties of the flux densities which were derived.

**stokes** : The names of the Stokes parameters which were derived.

**direction** : The reference code for **direction**, if not J2000.

**directionCode** : The direction to the source in celestial coordinates.

**directionEquinox** : The reference equinox for **direction**, if required by **directionCode**

**PA** : Position angle for source model.

**PAError** : Uncertainty on position angle for source model.

**size** : Half power sizes of source (main axes of ellipse).

**sizeError** : Uncertainties on half power size of source (main axes of ellipse)

**sourceModel** : Model used for source, e.g., point-like or Gaussian.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 32

### 1.15 CalFocus Table

Result of focus calibration performed on-line by TelCal.

CalFocus		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
receiverBand	ReceiverBand	identifies the receiver band.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of the result validity period.
endValidTime	ArrayTime	the end time of the result validity period.
ambientTemperature	Temperature	the ambient temperature.
atmPhaseCorrection	AtmPhaseCorrection	qualifies how the atmospheric phase correction has been applied.
focusMethod	FocusMethod	identifies the method used during the calibration.
frequencyRange	Frequency [2]	the frequency range over which the result is valid.
pointingDirection	Angle [2]	the antenna pointing direction (horizontal coordinates).
numReceptor	int	$N_{Recc}$ the number of receptors.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarization types (one value per receptor).
wereFixed	bool [3]	coordinates were fixed (true) or not fixed (false) (one value per individual coordinate).
offset	Length [ $N_{Rec}$ ] [3]	the measured focus offsets in X,Y,Z (one triple of values per receptor).
offsetError	Length [ $N_{Rec}$ ] [3]	the statistical uncertainties on measured focus offsets (one triple per receptor).
offsetWasTied	bool [ $N_{Rec}$ ] [3]	focus was tied (true) or not tied (false) (one value per receptor and focus individual coordinate).
reducedChiSquared	double [ $N_{Rec}$ ] [3]	a measure of the quality of the fit (one triple per receptor).
position	Length [ $N_{Rec}$ ] [3]	the absolute focus position in X,Y,Z (one triple of values per receptor).
<i>Optional Data</i>		
polarizationsAveraged	bool	Polarizations were averaged.
focusCurveWidth	Length [ $N_{Rec}$ ] [3]	half power width of fitted focus curve (one triple per receptor).





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 33

CalFocus – continued from previous page		
Name	Type (Shape)	Comment
focusCurveWidthError	Length [ $N_{Rec}$ ] [3]	Uncertainty of the focus curve width. each coordinate of the focus curve width was set (true) or not set (false) to an assumed value.
focusCurveWasFixed	bool [3]	
offIntensity	Temperature [ $N_{Rec}$ ]	the off intensity levels (one value per receptor).
offIntensityError	Temperature [ $N_{Rec}$ ]	the uncertainties on the off intensity levels (one value per receptor).
offIntensityWasFixed	bool	the off intensity level was fixed (true) or not fixed (false).
peakIntensity	Temperature [ $N_{Rec}$ ]	the maximum intensities (one value per receptor).
peakIntensityError	Temperature [ $N_{Rec}$ ]	the uncertainties on the maximum intensities (one value per receptor).
peakIntensityWasFixed	bool	the maximum intensity was fixed (true) or not fixed (false).

### Column Descriptions:

- antennaName : Refers uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.
- receiverBand : The name of the front-end frequency band being used.
- calDataId : CalData Table identifier.
- calReductionId : CalReduction Table identifier.
- startValidTime : The start of the time validity range for the result.
- endValidTime : The end of the time validity range for the result.
- ambientTemperature : Ambient temperature at the time of measurement. For mm-wave antennas a temperature dependence of the focus correction is expected.
- atmPhaseCorrection : The atmospheric phase correction states for which result is given.
- focusMethod : Method used, e.g., 'Interferometry' or '5 points'
- frequencyRange : Frequency range over which the result is valid. **Frequency reference: TOPO**
- pointingDirection : The antenna pointing direction (horizontal coordinates). For mm-wave antennas an elevation dependence of the focus correction is expected. **Direction Reference: AZEL (Epoch: NOW, Position: Antenna.position)**
- numReceptor : Number of receptors.
- polarizationTypes : The relevant polarizations for the measured focus parameters.
- wereFixed : Indicates which focus coordinates were kept fixed during measurement (and thus were not measured).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 34

**offset** : The measured focus offsets in X, Y, Z. This offset is relative to the nominal position of the focus, once the focus model has been applied.

**offsetError** : Uncertainty of **offset**.

**offsetWasTied** : True for a polarization and focus coordinate when this quantity was assumed fixed relative to the corresponding coordinate in the other polarization.

**reducedChiSquared** : Reduced  $\chi^2$  indicating the quality of the least-squares fit.

**polarizationsAveraged** : Set when polarizations were averaged over to improve sensitivity.

**position** : the absolute focus position in X,Y,Z (one triple of values per receptor). In addition to **offset** this includes the focus model value.

**focusCurveWidth** : Half-power width of fitted focus curve.

**focusCurveWidthError** : Statistical uncertainty of the half-power width of the fitted focus curve.

**focusCurveWasFixed** : Indicates that the half-power width of the fitted focus curve was fixed to an assumed value.

**offIntensity** : Off intensity level. This is needed for completeness to define the fitted beam function whenever the off level is non-zero (single-dish pointing).

**offIntensityError** : Off intensity level uncertainty

**offIntensityWasFixed** : Off intensity level was fixed.

**peakIntensity** : Fitted maximum intensity of signal.

**peakIntensityError** : Statistical uncertainty of the fitted maximum signal intensity.

**peakIntensityWasFixed** : Indicates that the maximal signal intensity was fixed to an assumed value.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 35

### 1.16 CalFocusModel Table

Result of focus model calibration performed by TelCal.

CalFocusModel		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
receiverBand	ReceiverBand	identifies the receiver band.
polarizationType	PolarizationType	identifies the polarization type for which this focus model is valid.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
antennaMake	AntennaMake	identifies the antenna make.
numCoeff	int	$N_{Coeff}$ the number of coefficients.
numSourceObs	int	$N_{Source}$ the number of source directions observed to derive the model.
coeffName	string [ $N_{Coeff}$ ]	the names given to the coefficients in the model.
coeffFormula	string [ $N_{Coeff}$ ]	the coefficients formula (one string per coefficient).
coeffValue	float [ $N_{Coeff}$ ]	the fitted values of the coefficients.
coeffError	float [ $N_{Coeff}$ ]	the statistical uncertainties on the derived coefficients (one value per coefficient).
coeffFixed	bool [ $N_{Coeff}$ ]	one coefficient was fixed (true) or not fixed (false) (one boolean value per coefficient).
focusModel	string	the name of this focus model.
focusRMS	Length [3]	the RMS deviations of residuals of focus coordinates.
reducedChiSquared	double	a measure of the quality of the least-square fit.

#### Column Descriptions:

antennaName : Refers uniquely to the hardware antenna object, as present in the original SDM Antenna table.

receiverBand : The name of the front-end frequency band being used.

polarizationType : Polarization component for which the focus model is valid.

calDataId : CalData Table identifier.

calReductionId : CalReduction Table identifier.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 36

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**antennaMake** : The antenna make (e.g., for ALMA, the manufacturer name such as AEC, Vertex, or Melco).

**numCoeff** : Number of coefficients in the focus model.

**numSourceObs** : Number of source directions observed to derive the model.

**coeffName** : The given names of the coefficients in the model.

**coeffFormula** : The formula describing the fitted functional dependence for the focus coordinate.

**coeffValue** : The fitted value for the coefficient.

**coeffError** : The statistical uncertainty on the derived coefficients.

**coeffFixed** : A boolean specifying that the coefficient was fixed to an assumed value.

**focusModel** : Name of this focus model.

**focusRMS** : The root mean square deviation of residuals in focus coordinates.

**reducedChiSquared** : Reduced  $\chi^2$  indicating the quality of the least-squares fit.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 37

### 1.17 CalGain Table

This Table is a placeholder to be used to wrap up casa gain tables produced in the Science Pipeline and Offline so that they can be archived in the ALMA Calibration Data Base.

CalGain		
Name	Type (Shape)	Comment
<i>Key</i>		
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReductionTable.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
gain	float	TBD
gainValid	bool	TBD
fit	float	TBD
fitWeight	float	TBD
totalGainValid	bool	TBD
totalFit	float	TBD
totalFitWeight	float	TBD

#### Column Descriptions:

calDataId : CalData Table identifier.

calReductionId : CalReduction Table identifier.

startValidTime : The start of the time validity range for the result.

endValidTime : The end of the time validity range for the result.

gain : TBD

gainValid : TBD

fit : TBD

fitWeight : TBD

totalGainValid : TBD

totalFit : TBD

totalFitWeight : TBD



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 38

### 1.18 CalHolography Table

Result of holography calibration performed by TelCal.

CalHolography		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
antennaMake	AntennaMake	identifies the antenna make.
startValidTime	ArrayTime	Start time of result validity period
endValidTime	ArrayTime	the end time of result validity period.
ambientTemperature	Temperature	the ambient temperature.
focusPosition	Length [3]	the focus position.
frequencyRange	Frequency [2]	the range of frequencies for which the measurement is valid.
illuminationTaper	double	the amplitude illumination taper.
numReceptor	int	$N_{Rec}$ the number of receptors.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarization types (one value per receptor).
numPanelModes	int	$N_{Panc}$ the number panel modes fitted.
receiverBand	ReceiverBand	identifies the receiver band.
beamMapUID	EntityId	refers to the beam map image.
rawRMS	Length	the RMS of the pathlength residuals.
weightedRMS	Length	the weighted RMS of the pathlength residuals.
surfaceMapUID	EntityId	refers to the resulting antenna surface map image.
direction	Angle [2]	the direction of the source.
<i>Optional Data</i>		
numScrew	int	$N_{Scre}$ the number of screws.
screwName	string [ $N_{Scr}$ ]	the names of the screws (one value per screw).
screwMotion	Length [ $N_{Scr}$ ]	the prescribed screw motions (one value per screw).
screwMotionError	Length [ $N_{Scr}$ ]	the uncertainties on the prescribed screw motions (one value per screw).
gravCorrection	bool	indicates if a gravitational correction was applied (true) or not (false).
gravOptRange	Angle [2]	the range of gravitational optimization.
tempCorrection	bool	indicates if a temperature correction was applied (true) or not (false).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 39

### CalHolography – continued from previous page

Name	Type (Shape)	Comment
tempOptRange	Temperature [2]	the range of temperature optimization.

#### Column Descriptions:

**antennaName** : Refers uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.

**calDataId** : CalData Table identifier.

**calReductionId** : CalReduction Table identifier.

**antennaMake** : The antenna make (e.g., for ALMA, the manufacturer name such as AEC, Vertex, or Melco).

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**ambientTemperature** : Ambient temperature at the time of measurement. The surface deformations are expected to depend on temperature.

**focusPosition** : The optimal focus position (in XYZ) as derived from the aperture map phases. **Position Reference: REFLECTOR**

**frequencyRange** : Frequency range over which the result is valid. **Frequency reference: TOPO**

**illuminationTaper** : Power illumination taper assumed to calculate weighted rms.

**numReceptor** : The number or polarization receptors (one or two) for which the result is given.

**polarizationTypes** : The polarization types of the receptors being used.

**numPanelModes** : The number of panel independent position/deformation modes that have been fitted.

**receiverBand** : The name of the front-end frequency band being used.

**beamMapUID** : The beam map UID provides a link to the resulting beam map image either as a disk file or in the ALMA Archive. The disk file name is built from the UID string by replacing all colons and slashes by underscores.

**rawRMS** : The root mean square of the pathlength residuals, measured along Z, that is perpendicular to the aperture plane when looking a source at infinite distance.

**weightedRMS** : The root mean square of pathlength residuals (along Z); weighted assuming a primary beam illumination as specified by **illuminationTaper**.

**surfaceMapUID** : The surface map UID provides a link to the resulting antenna surface map image either as a disk file or in the ALMA Archive. The disk file name is built from the UID string by replacing all colons and slashes by underscores.

**direction** : The antenna pointing direction (horizontal coordinates) **Direction Reference: AZEL (Epoch: NOW, Position: Antenna.position)**

**numScrew** : Number of screws to be adjusted using surface map data.

**screwName** : The string identification of the panel screws.

**screwMotion** : The prescribed panel screw adjustments derived from the panel fit to the aperture map phases.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 40

**screwMotionError** : The statistical uncertainties on the prescribed panel screw adjustments derived from the panel fit to the aperture map phases.

**gravCorrection** : Optimization target elevation range for the gravitaionnal correction applied.

**gravOptRange** : Optimization target elevation range for the gravitaionnal correction applied.

**tempCorrection** : A temperature correction was applied in the screw motion data.

**tempOptRange** : Optimization target temperature range.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 41

### 1.19 CalPhase Table

Result of the phase calibration performed by TelCal.

CalPhase		
Name	Type (Shape)	Comment
<i>Key</i>		
basebandName	BasebandName	identifies the baseband.
receiverBand	ReceiverBand	identifies the receiver band.
atmPhaseCorrection	AtmPhaseCorrection	describes how the atmospheric phase correction has been applied.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
numBaseline	int	$N_{Base}$ the number of baselines.
numReceptor	int	$N_{Recc}$ the number of receptors.
ampli	float [ $N_{Rec}$ ] [ $N_{BL}$ ]	the amplitudes (one value per receptor per baseline).
antennaNames	string [ $N_{BL}$ ] [2]	the names of the antennas (one pair of strings per baseline).
baselineLengths	Length [ $N_{BL}$ ]	the physical lengths of the baselines (one value per baseline).
decorrelationFactor	float [ $N_{Rec}$ ] [ $N_{BL}$ ]	the decorrelation factors (one value per receptor per baseline).
direction	Angle [2]	the direction of the source.
frequencyRange	Frequency [2]	the frequency range over which the result is valid.
integrationTime	Interval	the integration duration for a data point.
phase	float [ $N_{Rec}$ ] [ $N_{BL}$ ]	the phases of the averaged interferometer signal (one value per receptor per baseline).
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarization types of the receptors (one value per receptor).
phaseRMS	float [ $N_{Rec}$ ] [ $N_{BL}$ ]	the RMS of phase fluctuations relative to the average signal (one value per receptor per baseline).
statPhaseRMS	float [ $N_{Rec}$ ] [ $N_{BL}$ ]	the RMS of phase deviations expected from the thermal fluctuations (one value per receptor per baseline).
<i>Optional Data</i>		



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 42

CalPhase – continued from previous page		
Name	Type (Shape)	Comment
correctionValidity	bool [ $N_{BL}$ ]	the deduced validity of atmospheric path length correction (from water vapor radiometers).

### Column Descriptions:

**basebandName** : The name of the 'baseband pair' which is measured. For ALMA, a baseband pair is the signal path identified by a second local oscillator and has two polarizations.

**receiverBand** : The name of the front-end frequency band being used.

**atmPhaseCorrection** : The atmospheric phase corrections states for which result is given.

**calDataId** : CalData Table identifier.

**calReductionId** : CalReduction Table identifier.

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**numBaseline** : Number of baselines for which the result is given.

**numReceptor** : The number or polarization receptors (one or two) for which the result is given.

**ampli** : Amplitude of averaged signal.

**antennaNames** : Refer uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.

**baselineLengths** : The physical length of each baseline.

**decorrelationFactor** : The calculated decorrelation factor (amplitude loss) due to non-thermal phase fluctuations.

**direction** : The antenna pointing direction in horizontal coordinates. **Direction Reference: AZEL (Epoch: NOW, Position: Antenna.position)**

**frequencyRange** : Frequency range over which the result is valid **Frequency reference: TOPO**

**integrationTime** : Integration time on a data point, to calculate rms.

**phase** : The phase of the averaged interferometer signal.

**polarizationTypes** : The polarization types of the receptors being used.

**phaseRMS** : The root mean square of phase fluctuations relative to the average signal.

**statPhaseRMS** : The root mean square of phase deviations expected from thermal fluctuations.

**correctionValidity** : Deduced validity of atmospheric path length correction (from Water Vapour Radiometers; remark: It is not clear that correctionValidity is really an array. What about its size?).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 43

### 1.20 CalPointing Table

Result of the pointing calibration performed on-line by TelCal.

CalPointing		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	Antenna Name
receiverBand	ReceiverBand	identifies the receiver band.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
ambientTemperature	Temperature	the ambient temperature.
antennaMake	AntennaMake	identifies the antenna make.
atmPhaseCorrection	AtmPhaseCorrection	describes how the atmospheric phase correction has been applied.
direction	Angle [2]	the antenna pointing direction.
frequencyRange	Frequency [2]	the frequency range over which the result is valid.
pointingModelMode	PointingModelMode	identifies the pointing model mode.
pointingMethod	PointingMethod	identifies the pointing method.
numReceptor	int	$N_{Rec}$ the number of receptors.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarizations types (one value per receptor).
collOffsetRelative	Angle [ $N_{Rec}$ ] [2]	the collimation offsets (relative) (one pair of angles per receptor).
collOffsetAbsolute	Angle [ $N_{Rec}$ ] [2]	the collimation offsets (absolute) (one pair of angles per receptor).
collError	Angle [ $N_{Rec}$ ] [2]	the uncertainties on collimation (one pair of angles per receptor)
collOffsetTied	bool [ $N_{Rec}$ ] [2]	indicates if a collimation offset was tied (true) or not tied (false) to another polar (one pair of boolean values per receptor).
reducedChiSquared	double [ $N_{Rec}$ ]	a measure of the quality of the least square fit.
<i>Optional Data</i>		
averagedPolarizations	bool	true when the polarizations were averaged together to improve sensitivity.
beamPA	Angle [ $N_{Rec}$ ]	the fitted beam position angles (one value per receptor).
beamPAError	Angle [ $N_{Rec}$ ]	the uncertainties on the fitted beam position angles (one value per receptor).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 44

CalPointing – continued from previous page		
Name	Type (Shape)	Comment
beamPAWasFixed	bool	indicates if the beam position was fixed (true) or not fixed (false).
beamWidth	Angle [ $N_{Rec}$ ] [2]	the fitted beam widths (one pair of angles per receptor).
beamWidthError	Angle [ $N_{Rec}$ ] [2]	the uncertainties on the fitted beam widths (one pair of angles per receptor).
beamWidthWasFixed	bool [2]	indicates if the beam width was fixed (true) or not fixed (true) (one pair of booleans).
offIntensity	Temperature [ $N_{Rec}$ ]	the off intensity levels (one value per receptor).
offIntensityError	Temperature [ $N_{Rec}$ ]	the uncertainties on the off intensity levels (one value per receptor).
offIntensityWasFixed	bool	indicates if the off intensity level was fixed (true) or not fixed (false).
peakIntensity	Temperature [ $N_{Rec}$ ]	the maximum intensities (one value per receptor).
peakIntensityError	Temperature [ $N_{Rec}$ ]	the uncertainties on the maximum intensities (one value per receptor).
peakIntensityWasFixed	bool	the maximum intensity was fixed.

### Column Descriptions:

**antennaName** : Refers uniquely to the hardware antenna object as present in the original **SDM** Antenna table.

**receiverBand** : The name of the front-end frequency band being used.

**calDataId** : CalData Table identifier.

**calReductionId** : CalReduction Table identifier.

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**ambientTemperature** : Ambient temperature at the time of measurement. For mm-wave antennas, a temperature dependence of the pointing correction may be expected.

**antennaMake** : The antenna make (e.g., for ALMA, the antenna manufacturer name such as AEC, Vertex, or Melco).

**atmPhaseCorrection** : The atmospheric phase correction states for which result is given.

**direction** : The antenna pointing direction (horizontal coordinates) **Direction Reference: AZEL (Epoch: NOW, Position: Antenna.position)**

**frequencyRange** : Frequency range over which the result is valid **Frequency reference: TOPO**

**pointingModelMode** : Radio pointing or Optical pointing.

**pointingMethod** : Observing method used to determine the collimation offsets.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 45

**numReceptor** : Number of receptors.

**polarizationTypes** : The relevant polarizations for the measured pointing parameters.

**collOffsetRelative** : The collimation offsets found required to center the source, relative to the expected direction of the source, using a predetermined pointing model. These are the collimation offsets to be applied for reference pointing, or for a more refined local pointing model. **DirectionOffset Reference: AZEL (Epoch: NOW, Position: Antenna.position; Origin: [virtual])**

**collOffsetAbsolute** : The collimation offsets found required to center the source, relative to the expected direction of the source assuming a perfect antenna mount. These are collimation offsets to be used for determination of the pointing model. **DirectionOffset Reference: AZEL (Epoch: NOW, Position: Antenna.position; Origin: target)**

**collError** : Statistical uncertainties in the determination of azimuth and elevation collimations.

**collOffsetTied** : True for a polarization coordinate when this quantity was assumed fixed relative to the corresponding coordinate in the other polarization.

**reducedChiSquared** : Reduced  $\chi^2$  indicating the quality of the least-squares fit.

**averagedPolarizations** : Set when polarizations were averaged together to improve sensitivity.

**beamPA** : Position angle of fitted antenna beam.

**beamPAError** : Statistical uncertainty of position angle of fitted antenna beam.

**beamPAWasFixed** : Indicates that the position angle of the fitted antenna beam was fixed to an assumed value.

**beamWidth** : Half-power width of fitted antenna beam.

**beamWidthError** : Statistical uncertainty of the half-power width of the fitted antenna beam.

**beamWidthWasFixed** : Indicates that the half-power width of antenna beam was fixed to an assumed value.

**offIntensity** : Off intensity level. This is needed for completeness to define the fitted beam function whenever the off level is non-zero (single-dish pointing).

**offIntensityError** : Off intensity level uncertainty.

**offIntensityWasFixed** : Off intensity level was fixed.

**peakIntensity** : Fitted maximum intensity of signal.

**peakIntensityError** : Statistical uncertainty of the fitted maximum signal intensity.

**peakIntensityWasFixed** : Indicates that the maximal signal intensity was fixed to an assumed value.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 46

### 1.21 CalPointingModel Table

Result of pointing model calibration performed by TelCal.

CalPointingModel		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
receiverBand	ReceiverBand	identifies the receiver band.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
antennaMake	AntennaMake	the antenna make.
pointingModelMode	PointingModelMode	identifies the pointing model mode.
polarizationType	PolarizationType	identifies the polarization type.
numCoeff	int	$N_{Coeff}$ the number of coefficients in the pointing model.
coeffName	string [ $N_{Coeff}$ ]	the names of the coefficients (one string per coefficient).
coeffVal	float [ $N_{Coeff}$ ]	the values of the coefficients resulting from the pointing model fitting (one value per coefficient).
coeffError	float [ $N_{Coeff}$ ]	the uncertainties on the pointing model coefficients (one value per coefficient).
coeffFixed	bool [ $N_{Coeff}$ ]	indicates if one coefficient was fixed (true) or not fixed (false) (one boolean per coefficient).
azimuthRMS	Angle	Azimuth RMS (on Sky)
elevationRms	Angle	Elevation rms (on Sky)
skyRMS	Angle	rms on sky
reducedChiSquared	double	measures the quality of the least square fit.
<i>Optional Data</i>		
numObs	int	$N_{Obs}$ the number of source directions observed to derive the pointing model.
coeffFormula	string [ $N_{Coeff}$ ]	formulas used for the fitting (one string per coefficient).

#### Column Descriptions:

antennaName : Refers uniquely to the hardware antenna object, as present in the original SDM Antenna table.

receiverBand : The name of the front-end frequency band being used.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 47

**calDataId** : CalData Table identifier.

**calReductionId** : CalReduction Table identifier.

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**antennaMake** : The antenna make (e.g., for ALMA, the manufacturer name such as AEC, Vertex, or Melco).

**pointingModelMode** : Pointing Model mode (Radio or optical)

**polarizationType** : Polarization component for which the pointing model is valid.

**numCoeff** : The number of coefficients in the pointing model.

**coeffName** : The names of the coefficients, following `tpoint` software conventions (generic functions, see `tpoint` software documentation by P. Wallace).

**coeffVal** : The fitted pointing model coefficients.

**coeffError** : Statistical uncertainties of pointing model coefficients.

**coeffFixed** : Indicates that the coefficient was kept fixed to an assumed value.

**azimuthRMS** : Root mean squared of azimuth residuals (as a true angle on the sky).

**elevationRms** : Root mean of squared elevation residuals (as a true angle on the sky).

**skyRMS** : Root mean squared of angular distance deviations.

**reducedChiSquared** : Reduced  $\chi^2$  indicating the quality of the least-squares fit.

**numObs** : The number of source directions observed used to derive the pointing model.

**coeffFormula** : Formula used. This describes the functions fitted, for the corresponding coefficient. This is useful when `tpoint` software has not been used.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 48

### 1.22 CalPosition Table

Result of antenna positions calibration performed by TelCal.

CalPosition		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
atmPhaseCorrection	AtmPhaseCorrection	describes how the atmospheric phase correction has been applied.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
antennaPosition	Length [3]	the position of the antenna.
stationName	string	the name of the station.
stationPosition	Length [3]	the position of the station.
positionMethod	PositionMethod	identifies the method used for the position calibration.
receiverBand	ReceiverBand	identifies the receiver band.
numAntenna	int	$N_{Ante}$ the number of antennas of reference.
refAntennaNames	string [ $N_{Ant}$ ]	the names of the antennas of reference (one string per antenna).
axesOffset	Length	the measured axe's offset.
axesOffsetErr	Length	the uncertainty on the determination of the axe's offset.
axesOffsetFixed	bool	the axe's offset was fixed (true) or not fixed (false).
positionOffset	Length [3]	the measured position offsets (a triple).
positionErr	Length [3]	the uncertainties on the measured position offsets (a triple).
reducedChiSquared	double	measures the quality of the fit.
<i>Optional Data</i>		
delayRms	double	the RMS deviation for the observed delays.
phaseRms	Angle	the RMS deviation for the observed phases.

#### Column Descriptions:

antennaName : Refers uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.

atmPhaseCorrection : The atmospheric phase correction states for which result is given.

calDataId : CalData Table identifier.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 49

`calReductionId` : CalReduction Table identifier.

`startValidTime` : The start of the time validity range for the result.

`endValidTime` : The end of the time validity range for the result.

`antennaPosition` : The antenna position measured values in the X, Y, Z horizontal system, relative to the station. **Position Offset Reference: AZEL; origin: Station.position**

`stationName` : The name of the station where the antenna was set.

`stationPosition` : The station position in the X, Y, Z geocentric system. These are included as references for `stationPosition`.

`positionMethod` : Position measurement method used (fit to delays or fit to phases).

`receiverBand` : The name of the front-end frequency band being used.

`numAntenna` : The number of antennas used as reference for the antenna with unknown position.

`refAntennaNames` : The names of the antennas used as reference to get the antenna unknown position.

`axesOffset` : Measured offsets between azimuth and elevation axes. This is the horizontal component perpendicular to the elevation axis, counted positive in the direction where the antenna is pointed at, when horizon-looking.

`axesOffsetErr` : Statistical uncertainties of measured offsets between azimuth and elevation axes.

`axesOffsetFixed` : The offsets between azimuth and elevation axes were held fixed at an assumed value.

`positionOffset` : The measured position offsets in the X, Y, Z horizontal system, relative to the values assumed at the time of observing and used to track the phases. **Position Offset Reference: AZEL; Origin: stationPosition**

`positionErr` : The statistical uncertainties of the measured position offsets in the X, Y, Z horizontal system. **Position Offset Reference: AZEL; Origin: stationPosition**

`reducedChiSquared` : Reduced  $\chi^2$  indicating the quality of the least-squares fit.

`delayRms` : The root mean squared deviations for the observed delays.

`phaseRms` : The root mean squared deviations for the observed phases.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 50

### 1.23 CalPrimaryBeam Table

Result of Primary Beam Map measurement.

CalPrimaryBeam		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
receiverBand	ReceiverBand	identifies the receiver band.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
antennaMake	AntennaMake	the antenna make.
frequencyRange	Frequency [2]	the range of frequencies over which the result is valid.
numReceptor	int	$N_{Rec}$ the number of receptors.
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarizations types of the receptors (one value per receptor).
mainBeamEfficiency	double [ $N_{Rec}$ ]	the main beam efficiency as derived from the beam map.
beamMapUID	EntityId	refers to the beam map image.
relativeAmplitudeRms	float	the RMS fluctuations in terms of the relative beam amplitude.

#### Column Descriptions:

antennaName : Refers uniquely to the hardware antenna object, as present in the original SDM Antenna table.

receiverBand : The name of the front-end frequency band being used.

calDataId : CalData Table identifier.

calReductionId : CalReduction Table identifier.

startValidTime : The start of the time validity range for the result.

endValidTime : The start of the time validity range for the result.

antennaMake : The antenna make (e.g., for ALMA, the manufacturer name such as AEC, Vertex, or Melco).

frequencyRange : Frequency range over which the result is valid. **Frequency reference: TOPO**

numReceptor : The number or polarization receptors (one or two) for which the result is given.

polarizationTypes : The polarization types of the receptors being used.

mainBeamEfficiency : The main beam efficiency as derived for the beam map.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 51

**beamMapUID** : URL of the beam map image. The beam map UID provides a link to the resulting beam map image (either as a disk file or in the ALMA Archive; the disk file name is built from the UID string by replacing all colons and slashes by underscores). This image is expected to have its own polarization axis and to be normalized to unity.

**relativeAmplitudeRms** : The root mean square fluctuations in terms of relative beam amplitude, i.e. the antenna gain scaled by its maximal value (on axis).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 52

### 1.24 CalReduction Table

Generic items describing the data reduction process.

CalReduction		
Name	Type (Shape)	Comment
<i>Key</i>		
calReductionId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
numApplied	int	$N_{Appl}$ the number of applied calibrations prior the reduction.
appliedCalibrations	string [ $N_{Appl}$ ]	the list of applied calibrations (one string per calibration).
numParam	int	$N_{Para}$ the number of listed parameters used for calibration.
paramSet	string [ $N_{Par}$ ]	the input parameters expressed as (keyword,value) pairs (one string per parameter).
numInvalidConditions	int	$N_{Inva}$ the number of invalidating conditions.
invalidConditions	InvalidatingCondition [ $N_{Inv}$ ]	invalidating use cases (one string per case).
timeReduced	ArrayTime	the epoch at which the data reduction was finished.
messages	string	messages issued by the data reduction software.
software	string	the name of the data reduction software reduction used.
softwareVersion	string	version information about the data reduction software used.

#### Column Descriptions:

calReductionId : CalReduction row identifier.

numApplied : The number of calibrations applied to data before solving for the result.

appliedCalibrations : List of calibrations applied before solving for the result.

numParam : The number of listed parameters as used for this calibration.

paramSet : The list of parameters needed to specify the calibration applied given as (keyword,value) pairs.

numInvalidConditions : The number of use cases that may invalidate the result.

invalidConditions : The list of use cases that may invalidate the result.

timeReduced : The epoch at which the data reduction was finished.

messages : Messages issued by the data reduction software.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 53

**software** : The name of the data reduction software used to derive the result.

**softwareVersion** : The version of the data reduction software used to derive the result.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 54

### 1.25 CalSeeing Table

The seeing parameters deduced from TelCal calibrations.

CalSeeing		
Name	Type (Shape)	Comment
<i>Key</i>		
atmPhaseCorrection	AtmPhaseCorrection	describes how the atmospheric phase correction has been applied.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to a unique row in CalReduction Table.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
frequencyRange	Frequency [2]	the range of frequencies over which this result is valid.
integrationTime	Interval	the duration of averaging for the evaluation of the RMS.
numBaseLengths	int	$N_{Base}$ the number of baselines for which the the RMS phase data is evaluated.
baselineLengths	Length [ $N_{Base}$ ]	the lengths of the baselines (one value per baseline).
phaseRMS	Angle [ $N_{Base}$ ]	the RMS of phase fluctuations (one value per baseline).
seeing	Angle	the seeing parameter, deduced for the LO1.
seeingError	Angle	the uncertainty on the seeing parameter.
<i>Optional Data</i>		
exponent	float	the exponent of the spatial structure function.
outerScale	Length	the outer scale.
outerScaleRMS	Angle	the RMS of phase fluctuations at scale length outerScale.

#### Column Descriptions:

atmPhaseCorrection : The atmospheric phase correction states for which result is given.

calDataId : CalData Table identifier.

calReductionId : CalReduction Table identifier.

startValidTime : The start of the time validity range for the result.

endValidTime : The end of the time validity range for the result.

frequencyRange : Frequency range over which the result is valid. **Frequency reference: TOPO**



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 55

**integrationTime** : Averaging time for evaluation of rms fluctuations.

**numBaseLengths** : The number of baselines for which the rms phase data is evaluated.

**baselineLengths** : The baseline lengths at which the phase rms is evaluated.

**phaseRMS** : Root mean squared phase fluctuations for each baseline length.

**seeing** : The seeing parameter deduced for the calculated rms phases. This is the half-power width of the beam that would be synthesized if those phase fluctuations were not corrected.

**seeingError** : The uncertainty on **seeing**.

**exponent** : The exponents of the fitted power laws in the phase rms data. There may be two values (inner, outer) if an outer scale is given.

**outerScale** : The outer scale of turbulence (validity limit of power law in phase structure function).

**outerScaleRMS** : Root mean squared phase fluctuations at scale length **outerScale**. This number allows to calculate the modelled phase structure function at any scale (above and below **outerScale**).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 56

### 1.26 CalWVR Table

Result of the water vapour radiometric calibration performed by TelCal.

CalWVR		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaName	string	the name of the antenna.
calDataId	Tag	refers to a unique row in CalData Table.
calReductionId	Tag	refers to unique row in CalReductionTable.
<i>Required Data</i>		
startValidTime	ArrayTime	the start time of result validity period.
endValidTime	ArrayTime	the end time of result validity period.
wvrMethod	WVRMethod	identifies the method used for the calibration.
numInputAntennas	int	$N_{Inpu}$ the number of input antennas (i.e. equipped with functional WVRs).
inputAntennaNames	string [ $N_{Inpu}$ ]	the names of the input antennas (one string per antenna).
numChan	int	$N_{Chan}$ the number of frequency channels in the WVR receiver.
chanFreq	Frequency [ $N_{Chan}$ ]	the channel frequencies (one value per channel).
chanWidth	Frequency [ $N_{Chan}$ ]	the widths of the channels (one value per channel).
refTemp	Temperature [ $N_{Inpu}$ ] [ $N_{Chan}$ ]	the reference temperatures (one value per input antenna per channel).
numPoly	int	$N_{Poly}$ the number of polynomial coefficients.
pathCoeff	float [ $N_{Inpu}$ ] [ $N_{Chan}$ ] [ $N_{Poly}$ ]	the path length coefficients (one value per input antenna per channel per polynomial coefficient).
polyFreqLimits	Frequency [2]	the limits of the interval of frequencies for which the path length coefficients are computed.
wetPath	float [ $N_{Poly}$ ]	The wet path as a function frequency (expressed as a polynomial).
dryPath	float [ $N_{Poly}$ ]	The dry path as a function frequency (expressed as a polynomial).
water	Length	The precipitable water vapor corresponding to the reference model.

#### Column Descriptions:





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 57

**antennaName** : Refers uniquely to the hardware antenna object, as present in the original **SDM** Antenna table.

**calDataId** : CalData Table identifier.

**calReductionId** : CalReduction Table identifier.

**startValidTime** : The start of the time validity range for the result.

**endValidTime** : The end of the time validity range for the result.

**wvrMethod** : Method used, e.g, ab initio, Empirical.

**numInputAntennas** : The number of antennas equipped with functional WVRs, from which the data should be interpolated, using the path length coefficients calculated, to obtain the pathlength correction to be applied to the antenna given as 'antennaName'.

**inputAntennaNames** :

**inputAntennaNames** : The names of the antennas equipped with functional WVRs, from which the data should be interpolated, using the path length coefficients calculated, to obtain the pathlength correction to be applied to the antenna given as 'antennaName'.

**numChan** : Number of frequency channels in the WVR receiver.

**chanFreq** : The center frequency of the WVR channels. **Frequency reference: TOPO**

**chanWidth** : The frequency width of the WVR channels.

**refTemp** : The reference temperature  $T_{Rcj}$  for each WVR channel to be used in the path length formula.

**numPoly** : The number of polynomial coefficients given, to obtain the frequency dependence of the pathlength correction.

**pathCoeff** : The path length coefficients to be used to obtain the pathlength correction to be applied to the antenna given as 'antennaName'. These are the coefficients  $C_{kcj}$  ( $k = 1, N_{Poly}$ ) used to obtain the path length as a linear combinations of the data from the  $N_{Chan}$  WVR channels (in temperature units). Each coefficient is a term of a polynomial expansion ( $N_{Poly}$  coefficients) of the predicted path length as a function of observing frequency in the astronomical band (frequency limits in PolyFreqLimits). These polynomials are Chebichev polynomials in this frequency interval reduced to  $[-1., 1.]$ . For the given Antenna (antennaName), the path length correction to be applied is:

$$\sum_{j=1, N_{InpA}} \left[ \sum_{c=1, N_{Chan}} P_{cj}(\nu)(T_{cj} - T_{Rcj}) \right]$$

where

- $T_{Rcj}$  is the reference WVR temperature for channel  $c$  of antenna  $j$
- $T_{cj}$  is the observed WVR temperature for channel  $c$  of antenna  $j$
- $P_{cj}(\nu)$  is the value of the Chebichev polynomial with coefficients evaluated at sky frequency  $\nu$  with coefficients  $C_{kcj}$  ( $k = 1, N_{Poly}$ )

In the most frequent case there is a single input antenna (AntennaName). If the WVR device on a given antenna is not available or fails, the above formula gives the desired way to interpolate the correction for that antenna, based of other antennas (close neighbours).

**polyFreqLimits** : Frequency limits of the frequency interval for which the path length coefficients are computed.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 58

**wetPath** : The wet path as a function of frequency expressed as Chebichev polynomial in the frequency range reduced to  $[-1, 1]$ . This corresponds to the reference model that reproduces the average line shape and is used in the delay server to track the phases and delays, while the departures from the average water line shape are used for the pathlength correction applied to the correlator.

**dryPath** : The dry path as a function of frequency expressed as a Chebicehv polynomial in the frequency range reduced to  $[-1, 1]$ . This corresponds to the same reference model as wetPath.

**water** : long doc missing



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 59

### 1.27 ConfigDescription Table

Defines the hardware configuration used to obtain the science data.

ConfigDescription		
Name	Type (Shape)	Comment
<i>Key</i>		
configDescriptionId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
numAntenna	int	$N_{Ante}$ the number of antennas.
numDataDescription	int	$N_{Data}$ the number of data descriptions.
numFeed	int	$N_{Feed}$ <b>The number of feeds used.</b>
correlationMode	CorrelationMode	identifies the correlation mode.
numAtmPhaseCorrection	int	$N_{AtmP}$ the number of descriptions of the atmospheric phase correction.
atmPhaseCorrection	AtmPhaseCorrection [ $N_{Atmp}$ ]	<b>The number of atmospheric phase correction states stored</b>
processorType	ProcessorType	identifies the generic processor's type.
spectralType	SpectralResolutionType	identifies the spectral type of the data.
antennaId	Tag [ $N_{Ant}$ ]	identifies numAntenna rows in AntennaTable.
feedId	int [ $N_{Ant} * \text{numFeed}$ ]	refers to many collections of rows in the Feed Table.
switchCycleId	Tag [ $N_{Data}$ ]	refers to a unique row in the SwitchCycle Table.
dataDescriptionId	Tag [ $N_{Data}$ ]	refers to one or more rows in DataDescriptionTable.
processorId	Tag	refers to a unique row in ProcessorTable.
<i>Optional Data</i>		
phasedArrayList	int [ $N_{Ant}$ ]	phased array identifiers.
numAssocValues	int	$N_{Assso}$ the number of associated config descriptions.
assocNature	SpectralResolutionType [ $N_{Assso}$ ]	the natures of the associations with other config descriptions (one value per association).
assocConfigDescriptionId	Tag [ $N_{Assso}$ ]	refers to one or more rows in ConfigDescriptionTable.

#### Column Descriptions:

configDescriptionId : Identifies the row in the Configuration Description Table.

numAntenna : The number of antennas used (given by the antennaId array).

numDataDescription : Number of data descriptions for this row. This is equal to the number of spectral windows.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 60

**numFeed** : The number of feeds used. Number of feeds (given by the **feedId** array). For ALMA, **numFeed** is always one and **feedId** is zero.

**correlationMode** : The correlation mode used; for ALMA this is either Autocorrelation only, or Correlation and Autocorrelation.

**numAtmPhaseCorrection** : **Number of Atmospheric Phase Correction states which are stored.**

**atmPhaseCorrection** : The atmospheric phase correction states of data given (corrected, uncorrected, or both).

**processorType** : The generic processor type, such as, e.g., CORRELATOR, SPECTROMETER, or RADIO-METER.

**spectralType** : The spectral type of this data. It may be e.g direct spectral processor data (at full resolution), or channel averaged spectral processor data, or total power detector data.

**antennaId** : The number of antennas used (given by the **antennaId** table).

**feedId** : Specifies which feed was used in the Feed Table.

**switchCycleId** : SwitchCycle Table identifier.

**dataDescriptionId** : DataDescription Table identifier.

**processorId** : The Processor Identifier provides a direct link to a row in the Processor Table.

**phasedArrayList** : List of phased array identifiers; normally not used for ALMA.

**numAssocValues** : The number of associated config descriptions.

**assocNature** : The nature of the associations established by the **assocConfigDescriptionId** array.

**assocConfigDescriptionId** : ConfigDescription Table identifier



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 61

### 1.28 CorrelatorMode Table

Contains information on a Correlator processor.

CorrelatorMode		
Name	Type (Shape)	Comment
<i>Key</i>		
correlatorModeId	Tag	refers to a unique row in the table.
<i>Required Data</i>		
numBaseband	int	$N_{Base}$ the number of basebands.
basebandNames	BasebandName [ $N_{BB}$ ]	identifies the basebands (one value per basebands).
basebandConfig	int [ $N_{BB}$ ]	encodes the basebands configurations (one value per baseband).
accumMode	AccumMode	identifies the accumulation mode.
binMode	int	the binning mode.
numAxes	int	$N_{Axes}$ the number of axes in the binary data blocks.
axesOrderArray	AxisName [ $N_{Axes}$ ]	the order of axes in the binary data blocks.
filterMode	FilterMode [ $N_{BB}$ ]	identifies the filters modes (one value per baseband).
correlatorName	CorrelatorName	identifies the correlator's name.

#### Column Descriptions:

**correlatorModeId** : Identifies the row in the Correlator Mode Table.

**numBaseband** : The number of baseband pairs used; this may be up to four for ALMA and the EVLA. A pair has two orthogonal polarization channels.

**basebandNames** : Baseband names, that is the baseband pairs that are used ; there are four for ALMA.

**basebandConfig** : Baseband Configuration; for ALMA currently expressed as a number like '103' for Time division mode, or '1' for tunable filter mode; there is one of these for each baseband pair.

**accumMode** : The accumulation mode: for ALMA this is either FAST (For 1ms dumps, autocorrelation only) or NORMAL (for 16ms minimum dumps, and simultaneous correlation and autocorrelation).

**binMode** : The number of data bins: data bins are used together for switch cycles. For instance we have two for frequency switching of nutator switching, but one only for interferometry.

**numAxes** : The number of axes in the binary data blocks.

**axesOrderArray** : The standard order of axes in the binary data blocks. Axes may be omitted (See the BDF documentation).

**filterMode** : The mode of operation of the digital filters used at the input of the ALMA correlator. These are the TDM (Time Division Mode) or TFB (Tunable Filter Bank) modes.

**correlatorName** : The name of the correlator; in ALMA we have the 'baseline' correlator and the 'ACA' correlator.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 62

### 1.29 DataDescription Table

Spectro-polarization description.

DataDescription		
Name	Type (Shape)	Comment
<i>Key</i>		
dataDescriptionId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
polOrHoloId	Tag	refers to a unique row in PolarizationTable or HolograpyTable.
spectralWindowId	Tag	refers to a unique row in SpectralWindowTable.

#### Column Descriptions:

dataDescriptionId : DataDescription Table identifier.

polOrHoloId : Polarization Table identifier or Holograpy Table identifier.

spectralWindowId : SpectralWindow Table identifier.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 63

### 1.30 DelayModel Table

Contains the delay model components.

DelayModel		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable. time interval for which the row's content is valid.
timeInterval	ArrayTimeInterval	
<i>Required Data</i>		
timeOrigin	ArrayTime	value used as the origin for the polynomials.
numPoly	int	$N_{Poly}$ the number of coefficients of the polynomials.
atmDryDelay	double [ $N_{Poly}$ ]	the dry atmospheric delay component.
atmWetDelay	double [ $N_{Poly}$ ]	the wet atmospheric delay.
clockDelay	double [ $N_{Poly}$ ]	the electronic delay.
geomDelay	double [ $N_{Poly}$ ]	the geometric delay.
<i>Optional Data</i>		
dispDelay	double [ $N_{Poly}$ ]	dispersive delay at 1m wavelength.
groupDelay	double [ $N_{Poly}$ ]	the group delay at 1m wavelength.
phaseDelay	double [ $N_{Poly}$ ]	the phase delay at 1m wavelength.

#### Column Descriptions:

**antennaId** : Antenna identifier, as indexed from an element in the antennaArray collection in the configDescription table.

**timeInterval** : Time interval for which the parameters in the row are valid. The same reference used for the Time column in the Main Table must be used.

**timeOrigin** : Origin for the polynomials.

**numPoly** : Series order for the delay time polynomial expansions.

**atmDryDelay** : Dry atmosphere delay component.

**atmWetDelay** : Wet atmosphere delay component.

**clockDelay** : Electronic delay.

**geomDelay** : Geometric delay.

**dispDelay** : Dispersive delay at 1m wavelength.

**groupDelay** : Group delay at 1m wavelength.

**phaseDelay** : Phase delay at 1m wavelength.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 64

### 1.31 Doppler Table

Doppler tracking information. This table defines how velocity information is converted into a frequency offset to compensate in real time for the Doppler effect. This table may be omitted for ALMA when the Doppler tracking is not corrected.

Doppler		
Name	Type (Shape)	Comment
<i>Key</i>		
dopplerId	int	identifies a collection of rows in the table. refers to a collection of rows in SourceTable.
sourceId	int	
<i>Required Data</i>		
transitionIndex	int	selects the transition in the source table for which the doppler tracking is done.
velDef	DopplerReferenceCode	identifies the definition of the velocity.
dopplerMode	DopplerTrackingMode	Mode used in Doppler tracking.

#### Column Descriptions:

dopplerId : Identifies the row in the Doppler Table.

sourceId : Identifies a source in the Source table.

transitionIndex : Identifies a particular spectral transition (for a source in the Source Table).

velDef : Velocity definition of the Doppler Shift, e.g. RADIO or OPTICAL. The value of the velocity is found in the Source Table as sysVel[transitionIndex]. (Doppler measure)

dopplerMode : Mode used in Doppler tracking.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 65

### 1.32 Ephemeris Table

At the present time, this table is not defined. **TO BE DEFINED AND IMPLEMENTED**

Ephemeris		
Name	Type (Shape)	Comment
<i>Key</i>		
ephemerisId	Tag	identifies a unique row in the table.
<i>Required Data</i>		

#### Column Descriptions:

ephemerisId : Identifies the Row in the Ephemeris Table.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 66

### 1.33 ExecBlock Table

Characteristics of the Execution block.

ExecBlock		
Name	Type (Shape)	Comment
<i>Key</i>		
execBlockId	Tag	identifies a unique row in ExecBlock Table.
<i>Required Data</i>		
startTime	ArrayTime	the start time of the execution block.
endTime	ArrayTime	the end time of the execution block.
execBlockNum	int	indicates the position of the execution block in the project (sequential numbering starting at 1).
execBlockUID	EntityId	the archive's UID of the execution block.
projectUID	EntityId	the archive's UID of the project.
configName	string	the name of the array's configuration.
telescopeName	string	the name of the telescope.
observerName	string	the name of the observer.
numObservingLog	int	<i>N<sub>Log</sub></i> the number of elements in the list of observing logs.
observingLog	EntityId[ <i>N<sub>Log</sub></i> ]	a list of references to the log(s) of the observation for this execution block.
sessionReference	EntityId	the observing session reference.
*DELETE* sbSummary	EntityId	refers to a row in SBSummaryTable. *DELETE*
baseRangeMin	Length	the length of the shortest baseline.
baseRangeMax	Length	the length of the longest baseline.
baseRmsMinor	Length	the minor axis of the representative ellipse of baseline lengths.
baseRmsMajor	Length	the major axis of the representative ellipse of baseline lengths.
basePa	Angle	the baselines position angle.
aborted	bool	the execution block has been aborted (true) or has completed (false).
numAntenna	int	<i>N<sub>Ante</sub></i> the number of antennas.
antennaId	Tag [ <i>N<sub>Ant</sub></i> ]	refers to the relevant rows in AntennaTable.
sBSummaryId	Tag	refers to a unique row in SBSummaryTable.
<i>Optional Data</i>		
releaseDate	ArrayTime	the date when the data go to the public domain.
*DELETE* flagRow	bool	this row is valid (false) or not valid (true).
ScaleId	Tag	refers to a unique row in ScaleTable.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 67

ExecBlock – continued from previous page		
Name	Type (Shape)	Comment
schedulerMode	string	the mode of scheduling.
siteAltitude	Length	the altitude of the site.
siteLongitude	Angle	the longitude of the site.
siteLatitude	Angle	the latitude of the site.
observingScript	string	the observing script used.

### Column Descriptions:

`execBlockId` : Identifies the row in the ExecBlock Table.

`startTime` : Scheduled time of start of data taking.

`endTime` : Scheduled time of end of data taking.

`execBlockNum` : Number of the ExecBlock: in ALMA Execution blocks in a project are consecutively numbered starting from 1.

`execBlockUID` : Archive UID of the ExecBlock (the container of the data set).

`projectUID` : The archive UID of the Project.

`configName` : Name of the array baseline configuration.

`telescopeName` : Name of the telescope (e.g. 'ALMA')

`observerName` : Name of the observer.

`observingLog` : Log of observations (information entered at execution time by the Operator).

`sessionReference` : This is useful for grouping execblocks. Data capture know the session reference so this information is easily available.

**\*DELETE\* sbSummary : SBSummary Table identifier \*DELETE\***

`schedulerMode` : Mode of the Scheduling when this data was taken (Dynamic, Interactive, ...)

`baseRangeMin` : Length of the minimum baseline. For ALMA this is expected to be filled from the unprojected baselines available in the array being used in this ExecBlock.

`baseRangeMax` : Length of the maximum baseline. For ALMA this is expected to be filled from the unprojected baselines available in the array being used in this ExecBlock.

`baseRmsMinor` : Minor axis of the representative ellipse of baseline lengths. For ALMA this is expected to be filled from the unprojected baselines available in the array being used in this ExecBlock. [Description of how this is to be calculated should be added here](#)

`baseRmsMajor` : Major axis of the representative ellipse of baseline lengths. For ALMA this is expected to be filled from the unprojected baselines available in the array being used in this ExecBlock. [Description of how this is to be calculated should be added here](#)

`basePa` : Position angle of the major axis on the representative ellipse of baseline lengths. For ALMA this is expected to be filled from the unprojected baselines available in the array being used in this ExecBlock.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 68

`siteAltitude` : Latitude of the site (array **reference** center).

`siteLongitude` : Longitude of the site (array **reference** center).

`siteLatitude` : Latitude of the site (array **reference** center).

`aborted` : Set when the execution was aborted.

`numAntenna` : Number of antennas used in the ExecBlock.

`antennaId` : Antenna Table identifier.

`sBSummaryId` : SBSummary Table identifier.

`releaseDate` : The date when the data will become public.

**\*DELETE\* flagRow** : Invalidates the row.\*DELETE\*

**observingScript** : The observing script used, expressed either as the EntityId of the observing script, or the text of the script itself.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 69

### 1.34 Feed Table

Contains characteristics of the feeds.

Feed		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable.
spectralWindowId	Tag	refers to a unique row in SpectralWindowTable.
timeInterval	ArrayTimeInterval	the time interval of validity of the content of the row.
feedId	int	identifies a collection of rows in the table.
<i>Required Data</i>		
numReceptor	int	$N_{Rec}$ the number of receptors.
beamOffset	double [ $N_{Rec}$ ] [2]	the offsets of the beam (one pair per receptor).
focusReference	Length [ $N_{Rec}$ ] [3]	the references for the focus position (one triple per receptor).
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	identifies the polarization types (one value per receptor).
polResponse	Complex [ $N_{Rec}$ ] [ $N_{Rec}$ ]	the polarization response (one value per pair of receptors).
receptorAngle	Angle [ $N_{Rec}$ ]	the receptors angles (one value per receptor).
receiverId	int [ $N_{Rec}$ ]	refers to one or more collections of rows in ReceiverTable.
<i>Optional Data</i>		
feedNum	int	the feed number to be used for multi-feed receivers.
illumOffset	Length [2]	the illumination offset.
position	Length [3]	the position of the feed.
beamId	Tag [ $N_{Rec}$ ]	refers for each receptor to a unique row in BeamTable.

#### Column Descriptions:

antennaId : Antenna Table identifier.

spectralWindowId : SpectralWindow Table identifier.

timeInterval : Time Interval of validity of the feed information.

feedId : Feed Table identifier.

numReceptor : The number of receptors for which the result is given.

beamOffset : Offset of the beam.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 70

`focusReference` : Reference for the focus position.

`polarizationTypes` : The polarization types of the receptors being used.

`polResponse` : The polarization response of the receptors.

`receptorAngle` : Position angle for X polarization direction.

`receiverId` : Points to the receivers corresponding to this feed.

`feedNum` : Feed number is to be used for multi-feed receivers (there are none in ALMA; so `feedNum` is always one).

`illumOffset` : Illumination offset for this feed, measured in linear distance from the center of the primary reflector. **Position Reference: REFLECTOR**

`position` : The position of the feed.

`beamId` : Points to the beam information corresponding to this feed.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 71

### 1.35 Field Table

The field position for each source.

Field		
Name	Type (Shape)	Comment
<i>Key</i>		
<b>fieldId</b>	<b>Tag</b>	identifies a unique row in the table.
<i>Required Data</i>		
<b>fieldName</b>	string	the name of the field.
<b>numPoly</b>	int	$N_{Poly}$ number of coefficients of the polynomials.
<b>delayDir</b>	Angle [ $N_{Poly}$ ] [2]	the delay tracking direction.
<b>phaseDir</b>	Angle [ $N_{Poly}$ ] [2]	the phase tracking direction.
<b>referenceDir</b>	Angle [ $N_{Poly}$ ] [2]	the reference direction.
<i>Optional Data</i>		
<b>time</b>	ArrayTime	value used as the origin for the polynomials.
<b>directionCode</b>	DirectionReferenceCode	the direction reference code of the field.
<b>directionEquinox</b>	ArrayTime	the direction reference equinox of the field.
<b>assocNature</b>	string	identifies the nature of the association with the row referred to by fieldId.
<b>ephemerisId</b>	Tag	refers to a unique row in EphemerisTable.
<b>sourceId</b>	int	refers to a collection of rows in SourceTable.
<b>assocFieldId</b>	Tag	Associated Field ID
<b>code</b>	string	describes the function of the field.

#### Column Descriptions:

**fieldId** : Field Table identifier.

**fieldName** : Name of this Field (usually a representative source, or one of several fields in a mosaic).

**code** : Used to identify the function of this field (target, calibration, etc.). Purely informative.

**numPoly** : Number of coefficients used for polynomial expansion of tracked directions.

**delayDir** : Direction in the sky for which delays due to Earth motion are compensated in real time **Direction Reference: directionCode (Epoch: directionEquinox)**

**phaseDir** : Direction in the sky for which phases due to Earth motion are tracked in real time. **Direction Reference: directionCode (Epoch: directionEquinox)**

**referenceDir** : Direction of reference.

- In Interferometry this is the correlated field center (common pointing direction for all antennas)

- In single dish this is the reference direction **Direction Reference: directionCode (Epoch: directionEquinox)**



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 72

`time` : Used as an origin for expansion polynomials for tracked directions.

`directionCode` : The common reference code for field directions in the row, if not J2000.

`directionEquinox` : The common reference equinox for field directions in the row, if required by `directionCode`.

`assocNature` : Gives the meaning of Associated Field rows.

`ephemerisId` : EphemerisTable identifier.

`sourceId` : Source Table identifier.

`assocFieldId` : Refers to a unique associate row in the table.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 73

### 1.36 Flag Table

This table is used for flagging visibility data and is used in addition to the Binary Data Format flags produced by the correlator software.

Flag		
Name	Type (Shape)	Comment
<i>Key</i>		
flagId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
startTime endTime reason numAntenna	ArrayTime ArrayTime string int	the start time of the flagging period. the end time of the flagging period. Extensible list of flagging conditions.
antennaId	Tag [ $N_{Ant}$ ]	$N_{Ante}$ The number of antennas to which the flagging refers. By convention numAntenna== 0 means that the flag applies to all the existing antennas. An array of Tag which refers to a collection of rows in the Antenna table. The flag applies to the antennas described in these rows. It is an error to have different elements with a same value in this array.
<i>Optional Data</i>		
numPolarizationType	int	$N_{Pola}$ The number of polarization types , i.e. the size of the attribute polarizationType. By convention numPolarizationType == 0 means that the flag applies to all the defined polarization types.
numSpectralWindow	int	$N_{Spec}$ The number of spectral windows. By convention numSpectralWindow == 0 means that the flag applies to all the existing spectral windows.
numPairedAntenna	int	$N_{Pair}$ The number of antennas to be paired with to form the flagged baselines. By convention, numPairedAntenna == 0 means that the flag applies to all baselines built on the antennas declared in the attribute antennaId.
polarizationType	PolarizationType [ $N_{Pola}$ ]	An array of values of type PolarizationType. It specifies the polarization types where the flagging applies. It is an error to have different elements with a same value in this array.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 74

### Flag – continued from previous page

Name	Type (Shape)	Comment
pairedAntennaId	Tag [ $N_{Pair}$ ]	An array of Tag which refers to rows in the Antenna table. These rows contain the description of the antennas which are paired to form the flagged baselines. It is an error to have distinct elements with a same value in this array.
spectralWindowId	Tag [ $N_{Spec}$ ]	An array of Tag which refers to a collection of rows in the SpectralWindow table. The flag applies to the spectral windows described in these rows. It is an error to have different elements with a same value in this array.

### Column Descriptions:

flagId : long doc missing  
 startTime : long doc missing  
 endTime : long doc missing  
 reason : long doc missing  
 numAntenna : long doc missing  
 antennaId : long doc missing  
 numPolarizationType : long doc missing  
 numSpectralWindow : long doc missing  
 numPairedAntenna : long doc missing  
 polarizationType : long doc missing  
 pairedAntennaId : long doc missing  
 spectralWindowId : long doc missing



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 75

### 1.37 Focus Table

Contains the focus information.

Focus		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId timeInterval	Tag ArrayTimeInterval	refers to a unique row in AntennaTable. time interval for which the row's content is valid.
<i>Required Data</i>		
focusTracking	bool	the focus motions have been tracked (true) or not tracked (false).
focusOffset	Length [3]	focus offset relative to the tracked position (a triple ).
focusRotationOffset	Angle [2]	focus rotation offset relative to the tracked position (tip, tilt).
focusModelId	int	refers to a collection of rows in FocusModelTable.
<i>Optional Data</i>		
measuredFocusPosition	Length [3]	the measured focus position.
measuredFocusRotation	Angle [2]	the measured focus rotation (tip, tilt).

#### Column Descriptions:

antennaId : Antenna Table identifier.

timeInterval : Time Interval of validity of the focus information.

focusTracking : Set if the subreflector was tracking the focus motions.

focusOffset : Focus offset introduced relative to the tracked position. **Position Offset Reference: AZEL;**  
**Origin: virtual**

focusRotationOffset : focus rotation offset relative to the tracked position (tip and tilt angles).

focusModelId : Specifies which Focus Model was used (FocusModel Table).

measuredFocusPosition : Measured Focus position. **Position Reference: REFLECTOR**

measuredFocusRotation : Measured Focus rotation: tip and tilt angles in radians.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 76

### 1.38 FocusModel Table

Contains the focus model data (function of elevation and temperature).

FocusModel		
Name	Type (Shape)	Comment
<i>Key</i>		
<b>antennaId</b>	<b>Tag</b>	refers to a unique row in AntennaTable.
<b>focusModelId</b>	<b>int</b>	refers to a collection of rows in the table.
<i>Required Data</i>		
<b>polarizationType</b>	<b>PolarizationType</b>	identifies the polarization type.
<b>receiverBand</b>	<b>ReceiverBand</b>	identifies the receiver band.
<b>numCoeff</b>	<b>int</b>	$N_{Coeff}$ the number of coefficients.
<b>coeffName</b>	<b>string</b> [ $N_{Coeff}$ ]	the names of the coefficients (one string per coefficient).
<b>coeffFormula</b>	<b>string</b> [ $N_{Coeff}$ ]	textual representations of the fitted functions (one string per coefficient).
<b>coeffVal</b>	<b>float</b> [ $N_{Coeff}$ ]	the values of the coefficients used (one value per coefficient).
<b>assocNature</b>	<b>string</b>	nature of the association with the row referred to by associatedFocusModelId.
<b>assocFocusModelId</b>	<b>int</b>	refers to a collection of rows in the table.

#### Column Descriptions:

**antennaId** : Antenna Table identifier.

**focusModelId** : Identifies the focus model.

**polarizationType** : Polarization component for which the focus model is valid.

**receiverBand** : The name of the front-end frequency band being used.

**numCoeff** : The number of coefficients in the analytical form of the model.

**coeffName** : Given names of coefficients.

**coeffFormula** : Analytical formula: explains the function fitted (e.g.  $\cos(el)$  or  $\ln(T)$ ).

**coeffVal** : The values of the coefficients used.

**assocNature** : Nature of associated focus model, e.g., receiver-specific, local, ...

**assocFocusModelId** : Associates another focus model used in addition. Used for the auxiliary pointing model (e.g. the local pointing model). The actual associated row is obtained by associating the current **antennaId** with **associatedFocusModelId** to form the key.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 77

### 1.39 FreqOffset Table

Frequency offset information. Contains an additional antenna-based frequency offset relative to the frequencies in the Spectral Windows. Useful for such thing as Doppler tracking.

FreqOffset		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable.
spectralWindowId	Tag	refers to a unique row in SpectralWindowTable.
timeInterval	ArrayTimeInterval	the time interval of validity of the row's content.
feedId	int	refers to a collection of rows in FeedTable.
<i>Required Data</i>		
offset	Frequency	frequency offset.

#### Column Descriptions:

antennaId : Antenna Table identifier.

spectralWindowId : SpectralWindow Table identifier.

timeInterval : Time Interval of validity of the frequency offset information.

feedId : Specifies which feed was used in the Feed Table.

offset : Frequency offset to be added to the frequency set in the spectral window Table.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 78

### 1.40 GainTracking Table

Gain tracking information. Contains variable control parameters affecting the signal coming from a receiver in an antenna. The number of LOs is in the Receiver table. See the document Antenna and Electronic Delay Calibration for details.

GainTracking		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable.
spectralWindowId	Tag	refers to a unique row in SpectralWindowTable.
timeInterval	ArrayTimeInterval	time interval for which the row's content is valid.
feedId	int	refers to a unique row in Feed Table
<i>Required Data</i>		
attenuator	float	the nominal value of the attenuator.
numLO	int	$N_{LO}$ the number of local oscillators.
numReceptor	int	$N_{Rece}$ the number of receptors.
cableDelay	double [ $N_{Rec}$ ]	the IF cable delay for each polarization (one value per receptor).
crossPolarizationDelay	double	the cross polarization delay.
loPropagationDelay	double [ $N_{LO}$ ]	the local oscillator propagation delays (one value per local oscillator).
polarizationTypes	PolarizationType [ $N_{Rec}$ ]	describes the polarizations of the receptors (one value per receptor).
receiverDelay	double [ $N_{Rec}$ ]	the receiver delays (one value per receptor).
<i>Optional Data</i>		
delayOffset	double	an antenna based delay offset.
freqOffset	Frequency [ $N_{LO}$ ]	an additional frequency offset applied to LOs (one value per LO)
phaseOffset	Angle [ $N_{LO}$ ]	an additional phase offset applied to LOs (one value per LO).
samplingLevel	float	the sampling level.
numAttFreq	int	$N_{AttF}$ the sizes of attSpectrum and attFreq.
attFreq	double [ $N_{AttF}$ ]	the attenuator frequencies.
attSpectrum	Complex [ $N_{AttF}$ ]	the attenuator's measured spectrum.

#### Column Descriptions:

antennaId : Antenna Table identifier.

spectralWindowId : SpectralWindow Table identifier.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 79

**timeInterval** : Time Interval of validity of the feed information.

**feedId** : Specifies which feed was used in the Feed Table.

**attenuator** : Gain due to the hardware attenuation selected for the Spectral window in this antenna. This is the nominal value of the attenuator.

**numLO** : The number of local oscillators.

**numReceptor** : The number of receptors.

**cableDelay** : The IF Cable delay for each polarization. This is measured e.g. using a low-frequency band, for which by convention the **receiverDelay** is set to zero.

**crossPolarizationDelay** : The Cross-Polarization Delay. Included here for completeness as it can be obtained also by differencing the delays for the two polarizations.

**loPropagationDelay** : Local oscillator propagation delay. Affects the data when the frequency is changed during observations (e.g. Doppler tracking).

**polarizationTypes** : The polarization types of the receptors being used.

**receiverDelay** : Receiver Delay for each polarization. By convention this can be set to zero for a low-frequency band (e.g. band 3).

**delayOffset** : Antenna-based delay offset: Any offset introduced on top on the delay model.

**freqOffset** : Antenna based frequency offset: Any offset introduced on top on the nominal LO frequencies (in the Receiver Table) and of the fringe tracking offsets based on the delay model (DelayModel Table).

- Offsets optionally added for Doppler tracking of celestial sources are part of the geometrical model and are separately kept in the FrequencyOffset table.
- The antenna-based offsets aimed at rejecting the unwanted side-bands.

**phaseOffset** : Antenna based phase offset: Any offset introduced on top on the model phase.

**samplingLevel** : Correlator sampling level. Cannot change for ALMA...

**numAttFreq** : Number of frequency points in **attSpectrum**

**attFreq** : Frequencies for the values in **attSpectrum**.

**attSpectrum** : Gain due to the hardware attenuation selected for the Spectral window in this antenna. This is the actual calibrated spectrum measured in the lab (complex values) as a function of frequency.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 80

### 1.41 Holography Table

Used for Single-Dish holography with a fixed transmitter.

Holography		
Name	Type (Shape)	Comment
<i>Key</i>		
<b>holographyId</b>	<b>Tag</b>	identifies a unique row in the table.
<i>Required Data</i>		
<b>distance</b>	<b>Length</b>	the distance to transmitter.
<b>focus</b>	<b>Length</b>	displacement of the feed from the primary nominal focus.
<b>numCorr</b>	<b>int</b>	$N_{Corr}$ the number of stored correlations.
<b>type</b>	<b>HolographyChannelType</b> [ $N_{Corr}$ ]	identifies the types of the correlation signals.

#### Column Descriptions:

**holographyId** : Identifies the row in the Holography Table.

**distance** : Distance from intersection of mount axes to transmitter.

**focus** : Displacement of signal feed from the primary nominal focus, used to compensate for the finite distance of transmitter.

**numCorr** : Number of correlations stored (3 autocorrelations, 3 correlations from the 3 receptors (signal feed, reference feed, quadrature signal feed)).

**type** : Identifies each of the numCorr correlation signals.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 81

### 1.42 Pointing Table

Antenna pointing information.

Pointing		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable.
timeInterval	ArrayTimeInterval	the time interval of validity of the row's content.
<i>Required Data</i>		
numSample	int	$N_{Samp}$ the number of time samples.
encoder	Angle [ $N_{Samp}$ ] [2]	Encoder values
pointingTracking	bool	the antenna was in tracking mode (true) or not (false).
usePolynomials	bool	use polynomials expansions (true) or not (false).
timeOrigin	ArrayTime	the value used as origin in the polynomials expansions.
numTerm	int	$N_{Term}$ the number of terms of the polynomials.
pointingDirection	Angle [ $N_{Term}$ ] [2]	the commanded pointing direction.
target	Angle [ $N_{Term}$ ] [2]	the direction of the target.
offset	Angle [ $N_{Term}$ ] [2]	Horizon mapping offsets
pointingModelId	int	refers to a collection of rows in Pointing-ModelTable.
<i>Optional Data</i>		
overTheTop	bool	pointing at elevations larger than 90 degrees (true) or lower (false).
sourceOffset	Angle [ $N_{Term}$ ] [2]	sources offsets (one pair per term of the polynomial).
sourceOffsetReferenceCode	DirectionReferenceCode	the direction reference code associated to the source offset.
sourceOffsetEquinox	ArrayTime	the equinox information (if needed by sourceReferenceCode).
sampledTimeInterval	ArrayTimeInterval [ $N_{Samp}$ ]	an array of ArrayTimeInterval which must be given explicitly as soon as the data are irregularly sampled.

#### Column Descriptions:

antennaId : Antenna Table identifier.

timeInterval : Time Interval of validity of the feed information.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 82

**numSample** : The number of time samples for **encoder**. The sampling intervals divide **timeInterval** into  $N_{Samp}$  contiguous intervals of equal duration. This is also used for the other direction columns (**offset**, **pointingDirection**, **target**, **sourceOffset**) when **usePolynomials** is **false**: in that case  $N_{Term} = N_{Samp}$ .

**encoder** : The values measured from the antenna. They may be however affected by metrology, if applied. Note that for ALMA this column will contain positions obtained using the AZ\_POSN\_RSP and EL\_POSN\_RSP monitor points of the ACU and not the GET\_AZ\_ENC and GET\_EL\_ENC monitor points (as these do not include the metrology corrections). It is agreed that the the vendor pointing model will never be applied.  
**Direction Reference: AZEL (Epoch: NOW; Position: Antenna.position)**

**pointingTracking** : Indicates that the antenna is in tracking mode.

**usePolynomials** : See **numSample** and **numTerm**.

**timeOrigin** : The time origin for polynomial expansions of **pointingDirection**, **target**, **offset**, and **sourceOffset**. Equal to the midpoint of **timeInterval** if  $N_{Term} = 1$ .

**numTerm** :

- If **usePolynomials** is **false**:  $N_{Term} = N_{Samp}$ , and the values in the direction columns (**offset**, **pointingDirection**, **target**, **sourceOffset**) correspond to the same sampling intervals used for **encoder**.
- If **usePolynomials** is **true**:  $N_{Term}$  is the number of terms in the polynomial expansion for the direction columns (**offset**, **pointingDirection**, **target**, **sourceOffset**). The time origin for these polynomials is **timeOrigin**.

**pointingDirection** : This is the commanded direction of the antenna. It is obtained by adding the **target** and **offset** columns, and then applying the pointing model referenced by **PointingModelId**. The pointing model can be the composition of the absolute pointing model and of a local pointing model. In that case their coefficients will both be in the **PointingModel** table.

**target** : This is the field center direction (as given in the Field Table), possibly affected by the optional antenna-based **sourceOffset**. This column is in horizontal coordinates. **Direction Reference: AZEL (Epoch: NOW; Position: Antenna.position)**

**offset** : Additional offsets in horizontal coordinates (usually meant for measuring the pointing corrections, mapping the antenna beam, ...). **DirectionOffset Reference: AZEL (Epoch: NOW; Position: Antenna.position, Origin: target)**

**pointingModelId** : Link to the pointing model applied.

**overTheTop** : The antenna is pointing at elevations larger than 90 degrees. Deprecated for ALMA, should not happen.

**sourceOffset** : Optionally, the antenna-based mapping offsets in the field. These are in the equatorial system, and used, for instance, in on-the-fly mapping when the antennas are driven independently across the field.

**sourceOffsetReferenceCode** : Source offset reference code, defaults to J2000.

**sourceOffsetEquinox** : Source offset equinox, if needed by **sourceOffsetReference**.

**sampledTimeInterval** : **long doc missing**



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 83

### 1.43 PointingModel Table

The pointing models used to point the antennas.

PointingModel		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable.
pointingModelId	int	pointingModel identifier
<i>Required Data</i>		
numCoeff	int	$N_{Coef}$ the number of coefficients used in the analytical form of the model.
coeffName	string [ $N_{Coef}$ ]	the names of the coefficients.
coeffVal	float [ $N_{Coef}$ ]	the values of the coefficients.
polarizationType	PolarizationType	identifies the polarization type.
receiverBand	ReceiverBand	identifies the receiver band.
assocNature	string	nature of the association with the row referred to by associatedPointingModelId.
assocPointingModelId	int	refers to a collection of rows in the table.
<i>Optional Data</i>		
coeffFormula	string [ $N_{Coef}$ ]	the fitted functions

#### Column Descriptions:

antennaId : Antenna Table identifier.

pointingModelId : Identifies the pointing model used.

numCoeff : The number of coefficients in the analytical form of the model.

coeffName : Standard names used by tpoint.

coeffVal : The values of the coefficients used.

polarizationType : Polarization component for which the pointing model is valid.

receiverBand : The name of the front-end frequency band being used.

assocNature : Nature of the associated pointing model: e.g. local pointing model, receiver-specific.

assocPointingModelId : Associates another pointing model used in addition. Used for the auxiliary pointing model (e.g. local pointing model, ...). The actual associated row is obtained by associating the current antennaId with associatedPointingModelId to form the key.

coeffFormula : Analytical formulae. This is not needed for ALMA as we use tpoint generic coefficients.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 84

### 1.44 Polarization Table

Polarization information.

Polarization		
Name	Type (Shape)	Comment
<i>Key</i>		
polarizationId	Tag	Polarization Table identifier
<i>Required Data</i>		
numCorr	int	$N_{Corr}$ Number of correlation products
corrType	StokesParameter [ $N_{Corr}$ ]	Correlation type
corrProduct	PolarizationType [ $N_{Corr}$ ] [2]	Correlation product.
<i>Optional Data</i>		
*DELETE* flagRow	bool	this row is valid (false) or not valid (true).

#### Column Descriptions:

polarizationId : Polarization Table identifier.

numCorr : The number of correlation products. This could be 1 (e.g. XX or YY), 2 (e.g. XX and YY), 3 (full polarization for auto-correlation), or 4 (full polarization for cross-correlation).

corrType : For each correlation product this indicates the Stokes type as defined in the Stokes parameters enumeration.

corrProduct : For each correlation product, a pair of integers, specifying the receptors from which the signal originated. The polarization of each receptor is defined in the polarizationType column in the Feed table. An example would be (0,0), (0,1), (1,0), (1,1) to specify all possible correlation products between two receptors.

\*DELETE\* flagRow : Invalidates the row. \*DELETE\*



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 85

### 1.45 Processor Table

Processor characteristics. This table holds summary information for the back-end processing devices used to generate the basic science data.

Processor		
Name	Type (Shape)	Comment
<i>Key</i>		
<code>processorId</code>	<code>Tag</code>	Processor identifier
<i>Required Data</i>		
<code>modeId</code>	<code>Tag</code>	refers to a unique row in CorrelatorModeTable or SquareLawDetectorTable or AlmaRadiometerTable.
<code>processorType</code>	<code>ProcessorType</code>	identifies the generic type of the processor.
<code>processorSubType</code>	<code>ProcessorSubType</code>	identifies the type of processor referred to by modeId.

#### Column Descriptions:

`processorId` : Processor Table identifier.

`modeId` : Processor table identifier.

`processorType` : The generic type of processor used.

`processorSubType` : Identifies the SDM table containing the processor-dependent information.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 86

### 1.46 Receiver Table

Receiver properties.

Receiver		
Name	Type (Shape)	Comment
<i>Key</i>		
receiverId	int	Receiver identifier
spectralWindowId	Tag	refers to a unique row in SpectralwindowTable.
timeInterval	ArrayTimeInterval	time interval for which the content is valid.
<i>Required Data</i>		
name	string	the name of the frontend.
numLO	int	$N_{LO}$ the number of frequencies of the local oscillator.
frequencyBand	ReceiverBand	identifies the band of frequencies.
freqLO	Frequency [ $N_{LO}$ ]	the frequencies of the local oscillator.
receiverSideband	ReceiverSideband	the receiver sideband used.
sidebandLO	NetSideband [ $N_{LO}$ ]	the sideband conversions.

#### Column Descriptions:

receiverId : Receiver Table identifier. Note that this is always zero for ALMA.

spectralWindowId : SpectralWindow Table identifier.

timeInterval : Time Interval of validity of the receiver information.

name : Name of the frontend.

numLO : The number of frequency changes in the receiver chain.

frequencyBand : The name of this frequency band (bands 1 to 10 for ALMA) These correspond to receiver cartridges in the ALMA dewars.

freqLO : Frequencies of the Local Oscillators in the receiving chain.

receiverSideband : The receiver sideband used.

sidebandLO : The sideband conversion for each of the local oscillators. Used to check the frequency plan.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 87

### 1.47 SBSummary Table

Characteristics of the Scheduling Block that has been executed. Much of the data here is reproduced from the Scheduling block itself.

SBSummary		
Name	Type (Shape)	Comment
<i>Key</i>		
sBSummaryId	Tag	refers to a unique row in the table.
<i>Required Data</i>		
sbSummaryUID	EntityId	the scheduling block archive's UID.
projectUID	EntityId	the projet archive's UID.
obsUnitSetUID	EntityId	the observing unit set archive's UID.
frequency	double	a representative frequency.
frequencyBand	ReceiverBand	the frequency band.
sbType	SBType	the type of scheduling block.
sbDuration	Interval	the duration of the scheduling block.
*Made                      Optional*	Angle [2]	the representative target direction.
centerDirection		
numObservingMode	int	$N_{Obse}$ the number of observing modes.
observingMode	string [ $N_{ObsM}$ ]	the observing modes.
numberRepeats	int	$N_{berR}$ the number of repeats.
numScienceGoal	int	$N_{Scie}$ the number of scientific goals.
scienceGoal	string [ $N_{SciG}$ ]	the scientific goals.
numWeatherConstraint	int	$N_{Weat}$ the number of weather constraints.
weatherConstraint	string [ $N_{WeaC}$ ]	the weather constraints.
<i>Optional Data</i>		
*Made                      Optional*	Angle [2]	the representative target direction.
centerDirection		
centerDirectionCode	DirectionReferenceCode	identifies the direction reference frame associated with centerDirection.
centerDirectionEquinox	ArrayTime	the equinox associated to centerDirection-ReferenceCode (if needed).

#### Column Descriptions:

sBSummaryId : Identifies each row of the SBSummary table.

sbSummaryUID : Archive UID of the scheduling block.

projectUID : Archive UID of the project.

obsUnitSetUID : Archive UID of the observing unit set.

frequency : Representative frequency.

frequencyBand : Frequency band used for the SB.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 88

**sbType** : Type of Scheduling Block (e.g. science, calibration, ...)

**sbDuration** : The duration of this SB (as planned).

**numObservingMode** : The number of observing modes.

**observingMode** : Standard observing mode, e.g. singleField, mosaic. One SB cannot have more than one standard observing mode. Examples: Single Field Interferometry, Pointed Mosaic, ...

**numberRepeats** : Number of executions scheduled for this SB.

**numScienceGoal** : Number of science goals.

**scienceGoal** : The science goals.

**numWeatherConstraint** : The number of weather constraints.

**weatherConstraint** : Weather scheduling constraints, as specified in the Observing Tool.

**centerDirection** : Direction of the representative target.

**centerDirectionCode** : The center direction reference code, if not J2000.

**centerDirectionEquinox** : The center direction reference equinox, if required by **centerDirectionCode**.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 89

### 1.48 \*NNEW\* Scale Table \*NEW\*

see also <http://almasw.hq.eso.org/almasw/bin/view/TELCAL/2010-03-03>

Scale		
Name	Type (Shape)	Comment
<i>Key</i>		
<b>scaleId</b>	<b>Tag</b>	Identifies an unique row in the table
<i>Optional Data</i>		
<b>timeScale</b>	<b>TimeScale</b>	The time scale used
<b>crossDataScale</b>	<b>DataScale</b>	Units of the CROSS_DATA binary component in the BDF.
<b>autoDataScale</b>	<b>DataScale</b>	Units of the AUTO_DATA binary component in the BDF.
<b>weights</b>	<b>WeightType</b>	Type of weighting

#### Column Descriptions:



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 90

### 1.49 Scan Table

A summary of information for each scan.

Scan		
Name	Type (Shape)	Comment
<i>Key</i>		
execBlockId	Tag	refers to a unique row in ExecBlockTable.
scanNumber	int	the scan number.
<i>Required Data</i>		
startTime	ArrayTime	the actual start time of the scan.
endTime	ArrayTime	the actual end time of the scan.
numIntent	int	$N_{Inte}$ the number of intents for this scan.
numSubscan	int	$N_{Subs}$ the number of subscans contained by this scan.
scanIntent	ScanIntent [ $N_{Inte}$ ]	identifies the intents of this scan.
calDataType	CalDataOrigin [ $N_{Inte}$ ]	identifies the calibration data types (one value per intent).
calibrationOnLine	bool [ $N_{Inte}$ ]	the online calibration was required (true) or not (false) (one value per intent).
*DELETE* flagRow	bool	this row is valid (false) or invalid (true).
<i>Optional Data</i>		
calibrationFunction	CalibrationFunction [ $N_{Inte}$ ]	identifies the calibration functions (one value per intent).
calibrationSet	CalibrationSet [ $N_{Inte}$ ]	attaches this scan to a calibration set (one value per intent).
calPattern	AntennaMotionPattern [ $N_{Inte}$ ]	identifies the antenna motion patterns used for the calibration.
numField	int	$N_{Fiel}$ the number of fields observed.
fieldName	string [ $N_{Fiel}$ ]	the names of the observed fields (one value per field).
sourceName	string	the name of the observed source.

#### Column Descriptions:

execBlockId : ExecBlock Table identifier.

scanNumber : The scan number. This increments starting from 1 in each Execution Block.

startTime : The time when this scan actually started acquiring data.

endTime : The time when this scan actually finished acquiring data.

numIntent : The scan intents for this scan.

numSubscan : The number of subscans used to achieve this scan.

scanIntent : The scan intents for this scan.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 91

`calDataType` : Calibration data type used for data reduction.

`calibrationOnLine` : True if on-line calibration was required.

**\*DELETE\* flagRow** : Invalidates the row. **\*DELETE\***

`calibrationFunction` : Function of the scan in the calibration set. This is used in on-line calibration.

`calibrationSet` : Identifies that the scan is part of a set of scans aimed at a particular calibration.

`calPattern` : Identifies the antenna motion pattern used for calibration; data reduction may use this information.

`numField` : The number of fields observed during this scan.

`fieldName` : The names of the fields observed during this scan.

`sourceName` : The name of the source observed (optional).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 92

### 1.50 Source Table

Summary of astronomical source information.

Source		
Name	Type (Shape)	Comment
<i>Key</i>		
sourceId	int	identifies a collection of rows in the table.
timeInterval	ArrayTimeInterval	the time interval of validity of the row's content.
spectralWindowId	Tag	refers to a unique row in SpectralWindowTable.
<i>Required Data</i>		
code	string	indicates the nature of the source.
direction	Angle [2]	the direction of the source.
properMotion	AngularRate [2]	the proper motion of the source.
sourceName	string	the name of the source.
<i>Optional Data</i>		
directionCode	DirectionReferenceCode	identifies the direction reference frame associated to direction.
directionEquinox	ArrayTime	the equinox associated to the direction reference frame (if required).
calibrationGroup	int	the calibration group number.
catalog	string	the name of the catalog.
deltaVel	Speed	the velocity resolution.
position	Length [3]	the position of the source.
numLines	int	$N_{Line}$ the number of line transitions.
transition	string [ $N_{Line}$ ]	the names of the transitions.
restFrequency	Frequency [ $N_{Line}$ ]	the rest frequencies (one value per transition line).
sysVel	Speed [ $N_{Line}$ ]	the systemic velocity.
rangeVel	Speed [2]	the velocity range.
sourceModel	SourceModel	identifies the source model.
frequencyRefCode	FrequencyReferenceCode	the frequency reference code.
numFreq	int	$N_{Freq}$ the number of frequencies.
numStokes	int	$N_{Stok}$ the number of Stokes parameters.
frequency	Frequency [ $N_{Freq}$ ]	the array of frequencies (one value per frequency).
frequencyInterval	Frequency [ $N_{Freq}$ ]	an array of frequency intervals (one value per interval).
stokesParameter	StokesParameter [ $N_{Stok}$ ]	the array of Stokes parameters (one value per parameter).
flux	Flux [ $N_{Freq}$ ] [ $N_{Stok}$ ]	the array of flux densities.
fluxErr	Flux [ $N_{Freq}$ ] [ $N_{Stok}$ ]	the array of uncertainties on flux densities.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 93

Source – continued from previous page		
Name	Type (Shape)	Comment
positionAngle	Angle [ $N_{Freq}$ ]	the major axis position angles (one value per frequency).
positionAngleErr	Angle [ $N_{Freq}$ ]	the uncertainties on major axis position angles.
size	Angle [ $N_{Freq}$ ] [2]	the sizes of source (one pair of values per frequency).
sizeErr	Angle [ $N_{Freq}$ ] [2]	the uncertainties on the source sizes (one pair of value per frequency).
velRefCode	RadialVelocityReferenceCode	the velocity reference for velocities.

### Column Descriptions:

sourceId : Identifies each row of the Source table.

timeInterval : Time Interval of validity of the source information.

spectralWindowId : SpectralWindow Table identifier.

code : Source code, e.g., Bandpass calibrator.

direction : The source direction, usually J2000. **Direction Reference: directionCode (Epoch: directionEquinox)**

properMotion : Source proper motion (change of direction with time).

sourceName : The source name (please respect UAI/IAU standard conventions).

directionCode : The source direction reference code, if not J2000.

directionEquinox : The source direction reference equinox, if required by directionCode.

calibrationGroup : Used to group sources for calibration purposes (kept for further use).

catalog : Gives the origin for source information if taken from a catalog.

deltaVel : Velocity resolution required for this source (from observer input; kept for further use).

position : Source position (when 3-dimensional information is available, like a local transmitter). **Baseline reference: ITRF**

numLines : Number of line transitions for which information is given.

transition : The line of each spectral line transition.

restFrequency : The rest frequency for each transition considered. **Frequency reference: LABREST**

sysVel : The source radial velocity in each of the line transitions. **Frequency reference: LSR**

rangeVel : Range of radial velocities present in the source (for spectroscopy).

sourceModel : A model for source.

frequencyRefCode : The reference code for frequency (if not LSRK)

numFreq : The number of frequencies for which parameters are provided.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 94

**numStokes** : The number of Stokes parameters that are provided at each frequency.

**frequency** : The list of frequencies for the flux densities **Frequency reference: TOPO**

**frequencyInterval** : The list of frequency intervals over which flux densities were measured.

**stokesParameter** : The array of Stokes parameters (one value per parameter).

**flux** : The values of fluxes provided.

**fluxErr** : The statistical uncertainties on the fluxes.

**positionAngle** : Position angles of the major axes for the elliptical sources.

**positionAngleErr** : Statistical uncertainties for the major axis position angles.

**size** : Source sizes measured along the major and minor axis.

**sizeErr** : Statistical uncertainties on the source sizes.

**velRefCode** : **the velocity reference code for velocities: sysVel, rangeVel, deltaVel.**



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 95

### 1.51 SpectralWindow Table

Spectral window description. The convention in ALMA is to describe the frequency axis in the topocentric reference frame. If this is not the case (for instance if active Doppler tracking is implemented) then `measFreqRef` should be set accordingly.

SpectralWindow		
Name	Type (Shape)	Comment
<i>Key</i>		
<code>spectralWindowId</code>	Tag	identifies a unique row in the table.
<i>Required Data</i>		
<code>basebandName</code>	BasebandName	identifies the baseband.
<code>netSideband</code>	NetSideband	identifies the net sideband.
<code>numChan</code>	int	$N_{Chan}$ the number of frequency channels.
<code>refFreq</code>	Frequency	the reference frequency.
<code>sidebandProcessingMode</code>	SidebandProcessingMode	identifies the sideband processing mode.
<code>totBandwidth</code>	Frequency	the total bandwidth.
<code>windowFunction</code>	WindowFunction	identifies the window function.
<i>Optional Data</i>		
<code>chanFreqStart</code>	Frequency	the frequency of the first channel.
<code>chanFreqStep</code>	Frequency	the increment between two successive frequencies.
<code>chanFreqArray</code>	Frequency [ $N_{Chan}$ ]	the frequencies defined as an array ( <code>numChan</code> values).
<code>chanWidth</code>	Frequency	the width of the frequency channel (supposedly constant).
<code>chanWidthArray</code>	Frequency [ $N_{Chan}$ ]	Array of channel widths
<code>correlationBit</code>	CorrelationBit	identifies the number of bits used in the signal representation.
<code>effectiveBw</code>	Frequency	the effective noise bandwidth.
<code>effectiveBwArray</code>	Frequency [ $N_{Chan}$ ]	array of effective bandwidths (one value per channel).
<code>freqGroup</code>	int	the frequency group number.
<code>freqGroupName</code>	string	the frequency group name.
<code>lineArray</code>	bool [ $N_{Chan}$ ]	indicates lines (true) versus baselines (false).
<code>measFreqRef</code>	FrequencyReferenceCode	the reference frame of the frequencies.
<code>name</code>	string	a name for this spectral window.
<code>oversampling</code>	int	<b>in Nyquist units (1 means no oversampling.</b>
<code>quantization</code>	bool	a quantization correction has been applied (true) or not applied (false).
<code>refChan</code>	double	the reference channel "number".
<code>resolution</code>	Frequency	the half power frequency resolution (supposedly constant for all the channels).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 96

SpectralWindow – continued from previous page		
Name	Type (Shape)	Comment
resolutionArray	Frequency [ $N_{Chan}$ ]	the frequency resolutions (possibly variable)(one value per channel).
numAssocValues	int	$N_{Asso}$ the number of associated values.
assocNature	SpectralResolutionType	the natures of the associations with the
assocSpectralWindowId	Tag [ $N_{Asso}$ ]	rows referred to by assocSpectralWindowId. refers to a collection of associated rows in the table.
imageSpectralWindowId	Tag	refers to a unique row in the table (image sideband description).
dopplerId	int	refers to a collection of rows in DopplerTable.

### Column Descriptions:

**spectralWindowId** : Identifies each row of the SpectralWindow table.

**basebandName** : Name of the baseband this spectral window is connected to.

**netSideband** : Equivalent sideband of spectrum frequency axis. Can be USB, LSB but also DSB , or NOSB (in the case of direct amplification).

**numChan** : The number of frequency channels.

**refFreq** : This is the reference frequency of the spectrum, it corresponds to the channel number **refChan** in the case of equidistant channels. This is normally set to the zero-frequency edge of the baseband, for correlation data, for compatibility with the Measurement Set. **Frequency reference: TOPO**

**sidebandProcessingMode** : In the case of single side band data, provides information on how side bands were separated, or how image sideband data was eliminated.

**totBandwidth** : The total bandwidth for the spectral window.

**windowFunction** : Indicates which window function was applied to the time-domain data before performing Fourier transform, for correlator data. Applying a window spectrum provides apodization of the spectral response to a monochromatic line.

**chanFreqStart** : The central frequency for the first channel of the spectrum. Used for regularly spaced frequencies. Either the couple (chanFreqStart, chanFreqStep) or chanFreqArray must be present. **Frequency reference: TOPO**

**chanFreqStep** : The channel frequency separation. Used for regularly spaced frequencies. Either the couple (chanFreqStart, chanFreqStep) or chanFreqArray must be present. **Frequency reference: TOPO**

**chanFreqArray** : The central frequency for each channel of the spectrum. Present for irregularly spaced frequencies. Either the couple (chanFreqStart, chanFreqStep) or chanFreqArray must be present. **Frequency reference: TOPO**

**chanWidth** : The channel width (at half power) of all channels. Used an array of identical channels. Either **chanWidth** or **chanWidthArray** must be present.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 97

**chanWidthArray** : The channel width at half power. Either **chanWidth** or **chanWidthArray** must be present.

**correlationBit** : Indicates how many bits were used to represent the signal to be correlated.

**effectiveBw** : The effective noise bandwidth of all channels in the spectrum (that is the white noise bandwidth that produces the same output noise fluctuations). Either **effectiveBw** or **effectiveBwArray** must be present.

**effectiveBwArray** : The array of effective noise bandwidth for each channel in the spectrum (that is the white noise bandwidth that produces the same output noise fluctuations). Either **effectiveBw** or **effectiveBwArray** must be present.

**freqGroup** : Frequency group number. Used to associate spectral windows for calibration purposes.

**freqGroupName** : Name of the frequency group. Used to associate spectral windows for calibration purposes.

**lineArray** : Indicates line vs. baseline. For channel averaged data, indicates the channels with line signal as opposed to the ones with baseline data. Used for single-dish spectral line pointing.

**measFreqRef** : The reference frame for frequencies (if not topocentric).

**name** : Name of this spectral window. **It would be very helpful for Pipeline applications if an ALMA spectral window naming convention could be defined, written by data capture, and copied by the filler to the measurement set spectral window. Something along the lines of WVR for WVR data, or 3mmUSB, or ...**

**oversampling** : **Oversampling relative to Nyquist sampling: 1 means no oversampling, 2 twiceNyquist, and so on (to improve signal to noise).**

**quantization** : True if the quantization correction has been applied to the data.

**refChan** : This is the channel number corresponding to the frequency **refFreq**. This is meaningful only for regularly spaced channels; it need not be an integer (for instance the reference frequency may fall between two channels if a half-channel is introduced in the correlator software).

**resolution** : The half-power width of the frequency channels. Used for identical channels. Either **resolution** or **resolutionArray** must be present.

**resolutionArray** : The array of half-power widths of the frequency channels. Either **resolution** or **resolutionArray** must be present.

**numAssocValues** : Number of associated spectral windows.

**assocNature** : Nature of association between spectral windows. In some cases two spectral windows are generated with the same data (full resolution and channel averaged); the association mechanism links these together.

**assocSpectralWindowId** : Associates another focus model used in addition. Used for the auxiliary pointing model (e.g. local pointing model, ...). The actual associated row is obtained by associating the current **antennaId** with **associatedFocusModelId** to form the key.

**imageSpectralWindowId** : The row in the SpectralWindow table which contains the description of the image sideband.

**dopplerId** : Doppler Table identifier.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 98

### 1.52 SquareLawDetector Table

Processor information for total power detectors.

SquareLawDetector		
Name	Type (Shape)	Comment
<i>Key</i>		
squareLawDetectorId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
numBand	int	$N_{Band}$ the number of bands.
bandType	DetectorBandType	identifies the band type.

#### Column Descriptions:

squareLawDetectorId : Identifies each row of the Square law detector table.

numBand : The number of band detectors.

bandType : Band type, e.g. BASEBAND (for ALMA there is also a detector higher in the chain, covering all basebands).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 99

### 1.53 State Table

State information.

State		
Name	Type (Shape)	Comment
<i>Key</i>		
stateId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
calDeviceName	CalibrationDevice	the name of the calibration device.
sig	bool	data to be used for signal measurement (true) or not (false).
ref	bool	data to be used for reference measurement (true) or not (false).
onSky	bool	the beam is on the sky (true) or not (false).
<i>Optional Data</i>		
weight	float	used for combining data.

#### Column Descriptions:

stateId : Identifies each row of the State table.

calDeviceName : Name of the calibration device (must be there if onSky is false).

sig : Data will be used for signal measurement.

ref : Data will be used for reference measurement.

onSky : True if the receiver is getting radiation from the sky.

weight : Weight to be used for combining data (useful when there are more than one signal or reference states).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 100

### 1.54 Station Table

Antenna station information.

Station		
Name	Type (Shape)	Comment
<i>Key</i>		
stationId	Tag	Station identifier.
<i>Required Data</i>		
name	string	the name of the station.
position	Length [3]	the position of the station.
type	StationType	identifies the type of the station.
<i>Optional Data</i>		
<b>time</b>	<b>ArrayTime</b>	<b>the time of position measurement.</b>

#### Column Descriptions:

stationId : Identifies each row of the Station table.

name : The name of the station.

position : The position of the station in geocentric frame of reference (X, Y, Z coordinates). **Position Reference: ITRF**

type : The station type, e.g. ANTENNA or WEATHER.

**time** : **the time of position measurement.**



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 101

### 1.55 Subscan Table

Subscan-based information.

Subscan		
Name	Type (Shape)	Comment
<i>Key</i>		
execBlockId	Tag	identifies a unique row in ExecBlockTable.
scanNumber	int	the number of the scan this subscan belongs to.
subscanNumber	int	the subscan number.
<i>Required Data</i>		
startTime	ArrayTime	the actual start time of the subscan.
endTime	ArrayTime	the actual end time of the subscan.
fieldName	string	the name of the observed field.
subscanIntent	SubscanIntent	the intent of the subscan.
numIntegration	int	$N_{berI}$ the number of integrations during the scan.
numSubintegration	int [ $N_{berI}$ ]	$N_{berS}$ the number of subintegrations for each integration.
*DELETE* flagRow	bool	True if row is flagged.
<i>Optional Data</i>		
subscanMode	SwitchingMode	identifies the data acquisition mode during the subscan.
correlatorCalibration	CorrelatorCalibration	identifies the correlator calibration during the subscan.

#### Column Descriptions:

execBlockId : ExecBlock Table identifier.

scanNumber : The scan number. This increments starting from 1 in each Execution Block.

subscanNumber : The subscans in a scan are numbered incrementally starting from 1 in each new scan.

startTime : The time when the subscan started collecting science data.

endTime : The time when the subscan finished collecting science data.

fieldName : The name of the field observed during this subscan.

subscanIntent : The intent for this subscan.

numIntegration : The number of integrations in this subscan.

numSubintegration : The number of sub-integrations in each one of the integrations of this subscan.

flagRow : Invalidates the row. \*DELETE\*

subscanMode : Describe the mode in which data was taken. Can be e.g. nutator switching, frequency switching, or no switching.

correlatorCalibration : Indicates whether this subscan is used for correlator internal calibration.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 102

### 1.56 SwitchCycle Table

Cycle information in switching modes. Describe each step in a switching cycle.

SwitchCycle		
Name	Type (Shape)	Comment
<i>Key</i>		
switchCycleId	Tag	identifies a unique row in the table.
<i>Required Data</i>		
numStep	int	$N_{Step}$ the number of steps.
weightArray	float [ $N_{Step}$ ]	the weights (one value per step).
dirOffsetArray	Angle [ $N_{Step}$ ] [2]	the pointing direction offsets (one pair per step).
freqOffsetArray	Frequency [ $N_{Step}$ ]	the frequencies offsets (one value per step).
stepDurationArray	Interval [ $N_{Step}$ ]	the duration of the steps (one value per steps).
<i>Optional Data</i>		
directionCode	DirectionReferenceCode	the reference frame associated to dirOffsetArray.t
directionEquinox	ArrayTime	the equinox associated to directionCode (if required).

#### Column Descriptions:

switchCycleId : Identifies each row of the Switch Cycle table.

numStep : The number of steps in the swtching cycle.

weightArray : Specify a weight to be used for each step of the switching cycle, when combining data (useful to differentiate signal and reference steps).

dirOffsetArray : Gives the pointing direction offsets in each step of the switching cycle. **Direction Reference: AZEL (Epoch: NOW; Position: Antenna.position)**

freqOffsetArray : Gives the frequency offsets in each step of the switching cycle.

stepDurationArray : The durations of the steps in the switching cycle.

directionCode : The reference frame associated to dirOffsetArray.

directionEquinox : The source direction reference equinox , if required by directionCode (e.g. being other than AZEL or J2000)



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 103

### 1.57 SysCal Table

System calibration. Gives information on the conversion of data to temperature scale. This table is reduced to follow the contents of the Measurement Set SysCal table. Use only spectral values (use a single channel spectral window for single numbers). `numChan` can be found in the SpectralWindow Table. The contents of this table are used to scale the data **in further processing**.

SysCal		
Name	Type (Shape)	Comment
<i>Key</i>		
<code>antennaId</code>	Tag	refers to a unique row in AntennaTable.
<code>spectralWindowId</code>	Tag	refers to a unique row in SpectralWindowTable.
<code>timeInterval</code>	ArrayTimeInterval	time interval for which the row's content is valid.
<code>feedId</code>	int	refers to a collection of rows in FeedTable.
<i>Required Data</i>		
<code>numReceptor</code>	int	$N_{Rece}$ the number of receptors.
<code>numChan</code>	int	$N_{Chan}$ the number of frequency channels.
<i>Optional Data</i>		
<code>tcalFlag</code>	bool	the calibration temperature flag.
<code>tcalSpectrum</code>	Temperature [ $N_{Rec}$ ] [ $N_{Chan}$ ]	the calibration temperatures (one value per receptor per channel).
<code>trxFlag</code>	bool	the receiver temperature flag.
<code>trxSpectrum</code>	Temperature [ $N_{Rec}$ ] [ $N_{Chan}$ ]	the receiver temperatures (one value per receptor per channel).
<code>tskyFlag</code>	bool	the sky temperature flag.
<code>tskySpectrum</code>	Temperature [ $N_{Rec}$ ] [ $N_{Chan}$ ]	the sky temperatures (one value per receptor per channel).
<code>tsysFlag</code>	bool	the system temperature flag.
<code>tsysSpectrum</code>	Temperature [ $N_{Rec}$ ] [ $N_{Chan}$ ]	the system temperatures (one value per receptor per channel).
<code>tantFlag</code>	bool	the tant flag.
<code>tantSpectrum</code>	float [ $N_{Rec}$ ] [ $N_{Chan}$ ]	the Tant spectrum (one value per receptor per channel).
<code>tantTsysFlag</code>	bool	the Tant/Tsys flag.
<code>tantTsysSpectrum</code>	float [ $N_{Rec}$ ] [ $N_{Chan}$ ]	the Tant/Tsys spectrum (one value per receptor per channel).
<code>phaseDiffFlag</code>	bool	the phase difference flag.
<code>phaseDiffSpectrum</code>	float [ $N_{Rec}$ ] [ $N_{Chan}$ ]	the phase difference spectrum (one value per receptor per channel).

#### Column Descriptions:



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 104

**antennaId** : Specifies which antenna was used in the Antenna Table.  
**spectralWindowId** : SpectralWindow Table identifier.  
**timeInterval** : Time Interval of validity of the SysCal information  
**feedId** : Specifies which feed was used in the Feed Table.  
**numReceptor** : The number of receptors.  
**numChan** : The number of frequency channels.  
**tcalFlag** : Calibration temperature flag.  
**tcalSpectrum** : Calibration temperature for each channel.  
**trxFFlag** : Receiver temperature flag.  
**trxSpectrum** : Receiver temperature for each channel.  
**tskyFlag** : Sky temperature flag.  
**tskySpectrum** : Sky temperature for each channel  
**tsysFlag** : System temperature flag.  
**tsysSpectrum** : System temperature for each channel.  
**tantFlag** : Tant Flag (MS compatibility).  
**tantSpectrum** : Tant Spectrum (MS compatibility).  
**tantTsysFlag** : Tant/Tsys Flag (MS compatibility).  
**tantTsysSpectrum** : Tant/Tsys Spectrum (MS compatibility).  
**phaseDiffFlag** : Phase Difference Flag (MS compatibility)  
**phaseDiffSpectrum** : Phase Difference Spectrum (MS compatibility)





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 105

### 1.58 SysPower Table

This table is intended to store power measurements based on a synchronous power detector as used at the EVLA. While the table is intended to be general enough for use with other arrays, it is deeply entwined with the EVLA data acquisition scheme. The units of  $P_{diff}$  and  $P_{sum}$  are such that the system temperature,  $T_{sys}$ , is :  $[T_{sys} = \frac{P_{sum}}{P_{diff}} \cdot \frac{T_{cal}}{2}]$  where  $T_{cal}$  is the temperature of the noise tube.

SysPower		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in the Antenna table.
spectralWindowId	Tag	refers to a unique row in the SpectralWindow table.
feedId	int	Refers to the collection of rows in the Feed table having this value of feedId in their key.
timeInterval	ArrayTimeInterval	time interval over which the content of the row was measured.
<i>Required Data</i>		
numReceptor	int	$N_{Rece}$ The number of receptors.
<i>Optional Data</i>		
switchedPowerDifference	float [ $N_{Rec}$ ]	the switched power difference $P_{diff}$ defined by $P_{diff} = G * (P_{on} - P_{off})$ .
switchedPowerSum	float [ $N_{Rec}$ ]	the switched power sum $P_{sum}$ defined by $P_{sum} = G(P_{on} + P_{off})$ .
requantizerGain	float [ $N_{Rec}$ ]	refers to the gain inserted after the synchronous power detector. For WIDAR, it is the requantizer gain ( $G$ ).

#### Column Descriptions:

antennaId : long doc missing

spectralWindowId : long doc missing

feedId : long doc missing

timeInterval : long doc missing

numReceptor : long doc missing

switchedPowerDifference : long doc missing

switchedPowerSum : long doc missing

requantizerGain : long doc missing



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 106

### 1.59 WVMCal Table

Coefficients to use water vapour monitor information to correct for pathlength variations. This contains the coefficients actually used, while CalWVR contains the coefficients derived from TelCal calibration.

WVMCal		
Name	Type (Shape)	Comment
<i>Key</i>		
antennaId	Tag	refers to a unique row in AntennaTable.
spectralWindowId	Tag	refers to a unique row in SpectralWindowTable.
timeInterval	ArrayTimeInterval	the time interval for which the row's content is valid.
<i>Required Data</i>		
wvrMethod	WVRMethod	identifies the calibration method.
polyFreqLimits	Frequency [2]	the range of frequencies in which the computation is performed.
numChan	int	$N_{Chan}$ the number of WVR channels.
numPoly	int	$N_{Poly}$ the number of coefficients used in the polynomial expansions.
pathCoeff	float [ $N_{Chan}$ ] [ $N_{Poly}$ ]	the pathlengths coefficients (one value per chan per coefficient).
refTemp	Temperature [ $N_{Chan}$ ]	the reference temperatures (one value per channel).

#### Column Descriptions:

antennaId : Antenna Table identifier.

spectralWindowId : SpectralWindow Table identifier.

timeInterval : Time Interval of validity of the Water Vapour information.

wvrMethod : Calibration method (see CalWVR table).

polyFreqLimits : Frequency limits of the frequency interval for which the path length coefficients are computed.

numChan : The number of WVR channels.

numPoly : Number of coefficients in polynomial expansion on frequency.

pathCoeff : Pathlength coefficients (see CalWVR table).

refTemp : Reference temperatures (see CalWVR table).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
 Date: February 24, 2011  
 Status: Draft  
 Page 107

### 1.60 Weather Table

Weather station information. For ALMA this may include rows from several standard weather stations, an oxygen sounder, a central WVR.

Weather		
Name	Type (Shape)	Comment
<i>Key</i>		
stationId	Tag	refers to a unique row in StationTable.
timeInterval	ArrayTimeInterval	the time interval for which the row's content is valid.
<i>Optional Data</i>		
pressure	Pressure	the ambient pressure.
*DELETE* pressureFlag	bool	the ambient pressure's value is invalid (true) or valid (false). *DELETE*
relHumidity	Humidity	the relative humidity.
*DELETE*	bool	the relative humidity's value is invalid (true) or valid (false). *DELETE*
relHumidityFlag		
temperature	Temperature	the ambient temperature.
*DELETE*	bool	the ambient temperature's value is invalid (true) or valid (false). *DELETE*
temperatureFlag		
windDirection	Angle	the wind direction.
*DELETE*	bool	the wind direction's value is invalid (true) or valid (false). *DELETE*
windDirectionFlag		
windSpeed	Speed	the wind speed.
*DELETE* windSpeedFlag	bool	the wind speed value is invalid (true) or valid (false). *DELETE*
windMax	Speed	the maximum wind speed
*DELETE* windMaxFlag	bool	the maximum wind speed value is invalid (true) or valid (false). *DELETE*
dewPoint	Temperature	the dew point's value.
*DELETE* dewPointFlag	bool	the dew point's value is invalid (true) or valid (false).
numLayer	int	$N_{Layer}$ the number of layers in the temperature profile
layerHeight	Length [ $N_{Layer}$ ]	the height of each layer for the temperature profile
temperatureProfile	Temperature [ $N_{Layer}$ ]	the temperature on the atmosphere at each height
cloudMonitor	Temperature	the temperature of the cloud monitor
numWVR	int	the number of WVR channels
wvrTemp	Temperature []	the observed temperature in each WVR channel
water	double	the water precipitable content



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 108

### Column Descriptions:

`stationId` : Station Table identifier.

`timeInterval` : Time Interval of validity of the weather information.

`pressure` : Ambient pressure (observatory ground level).

**\*DELETE\*** `pressureFlag` : Ambient pressure is invalid.

`relHumidity` : Relative humidity (related to dewpoint temperature).

**\*DELETE\*** `relHumidityFlag` : Relative humidity is invalid.

`temperature` : Ambient temperature.

**\*DELETE\*** `temperatureFlag` : Ambient temperature is invalid.

`windDirection` : Wind direction (counted East from North).

**\*DELETE\*** `windDirectionFlag` : Wind direction is invalid.

`windSpeed` : Average wind speed in interval.

**\*DELETE\*** `windSpeedFlag` : Average wind speed invalid.

`windMax` : Maximal wind speed in time interval.

**\*DELETE\*** `windMaxFlag` : Maximal wind speed was invalid.

`dewPoint` : Dewpoint temperature (related to humidity). This field should only be filled when the value is a primary measurement, and not when it is derived.

**\*DELETE\*** `dewPointFlag` : Dewpoint temperature is invalid

`numLayer` : The number of layers in the temperature profile. Needed if `temperatureProfile` is present.

`layerHeight` : The height of each layer for the temperature profile. Needed if `temperatureProfile` is present.

`cloudMonitor` : the temperature of the cloud monitor

`numWVR` : the number of WVR channels. Needed if `wvrTemp` is present.

`wvrTemp` : the observed temperature in each WVR channel

`water` : the water precipitable content



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 109

## 2 List of Enumerations



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 110

### 2.1 Versioning information for the enumerations.

- UML description : `/mnt/hgfs/Host/ALMA_CVS/HEAD/ICD/HLA/Enumerations/id1/ASDM_Enumerations.mzip`
- CVS revision : 1.9
- CVS branch : HEAD



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 111

### 2.2 ACAPolarization

version 1 ACA-specific ways to store pre-processed data products

ACA\_STANDARD : Data product is the standard way (it is a standard observed Stokes parameter)

ACA\_XX\_YY\_SUM : ACA has calculated I by averaging XX and YY

ACA\_XX\_50 : ACA has averaged XX and XX delayed by half a FFT period

ACA\_YY\_50 : ACA has averaged YY and YY delayed by half a FFT period

### 2.3 AccumMode

version 1 Accumulation modes for the Correlator

FAST : fast dump time. ALMA use case : 1 ms dump time, available only for autocorrelation.

NORMAL : normal dump time. ALMA use case : 16ms dump time, available for both autocorrelation and cross-orrelation.

UNDEFINED : Not defined or not applicable.

### 2.4 AntennaMake

version 1 The physical types of antenna

AEM\_12 : 12m AEM antenna

MITSUBISHI\_7 : 7-m Mitsubishi antenna (ACA)

MITSUBISHI\_12\_A : 12-m Mitsubishi antenna (ACA) (refurbished prototype)

MITSUBISHI\_12\_B : 12-m Mitsubishi antenna (ACA) (production)

VERTEX\_12\_ATF : 12-m Vertex antenna prototype

AEM\_12\_ATF : 12-m AEM antenna prototype

VERTEX\_12 : 12-m Vertex antenna

IRAM\_15 : 15-m IRAM antenna

UNDEFINED : Not defined or not applicable.

### 2.5 AntennaMotionPattern

version 1 Motion pattern of antenna , e.g. in a calibration scan.

NONE : No pattern.

CROSS\_SCAN : Crossed scan (continuous pattern)

SPIRAL : Spiral pattern

CIRCLE : Circular pattern

THREE\_POINTS : Three points pattern.

FOUR\_POINTS : Four points pattern.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 112

**FIVE\_POINTS** : Five points pattern.  
**TEST** : Reserved for development.  
**UNSPECIFIED** : Unspecified pattern.

### 2.6 AntennaType

version 1 Functional types of antenna  
**GROUND\_BASED** : Ground-based antenna  
**SPACE\_BASED** : Antenna in a spacecraft  
**TRACKING\_STN** : Space-tracking station antenna

### 2.7 AssociatedCalNature

version 1 These are the associated calibration natures  
**ASSOCIATED\_EXECBLOCK** : The associated execblock id concatenated to produce the data set

### 2.8 AssociatedFieldNature

version 1 [ASDM.Field] Nature of the associated field  
**ON** : The associated field is used as ON source data  
**OFF** : The associated field is used as OFF source data  
**PHASE\_REFERENCE** : The associated field is used as Phase reference data

### 2.9 AtmPhaseCorrection

version 1 Status of Phase correction  
**AP\_UNCORRECTED** : Data has no WVR phase correction  
**AP\_CORRECTED** : Data phases have been corrected using WVR data

### 2.10 AxisName

version 1 Axis names.  
**TIM** : Time axis.  
**BAL** : Baseline axis.  
**ANT** : Antenna axis.  
**BAB** : Baseband axis.  
**SPW** : Spectral window axis.  
**SIB** : Sideband axis.  
**SUB** : Subband axis.





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 113

BIN : Bin axis.  
APC : Atmosphere phase correction axis.  
SPP : Spectral point axis.  
POL : Polarization axis (Stokes parameters).  
STO : Stokes parameter axis.  
HOL : Holography axis.

### 2.11 BasebandName

version 1 Baseband names

NOBB : Baseband not applicable.  
BB\_1 : Baseband one  
BB\_2 : Baseband two  
BB\_3 : Baseband three  
BB\_4 : Baseband four  
BB\_5 : Baseband five (not ALMA)  
BB\_6 : Baseband six (not ALMA)  
BB\_7 : Baseband seven (not ALMA)  
BB\_8 : Baseband eight (not ALMA)  
BB\_ALL : All ALMA basebands (i.e. all available basebands)  
A1C1\_3BIT :  
A2C2\_3BIT :  
AC\_8BIT :  
B1D1\_3BIT :  
B2D2\_3BIT :  
BD\_8BIT :

### 2.12 BaselineReferenceCode

version 1 defines reference frames to qualify the measure of a baseline.

J2000 : mean equator, equinox J2000.0  
B1950 : mean equator, equinox B1950.0  
GALACTIC : galactic coordinates.  
SUPERGAL : supergalactic coordinates.  
ECLIPTIC : ecliptic for J2000.0  
JMEAN : mean equator.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 114

JTRUE : true equator.

APP : apparent geocentric.

BMEAN : mean equator.

BTRUE : true equator.

JNAT : geocentric natural frame.

MECLIPTIC : ecliptic for mean equator.

TECLIPTIC : ecliptic for true equator.

TOPO : apparent geocentric

MERCURY : from JPL DE table.

VENUS :

MARS :

JUPITER :

SATURN :

NEPTUN :

SUN :

MOON :

HADEC :

AZEL :

AZELGEO :

AZELSW : topocentric Az/El ( $N = i$  E).

AZELNE : idem AZEL.

ITRF : ITRF earth frame.

### 2.13 CalCurveType

version 1 [CalDM.CalCurve] type pf calibration curve

AMPLITUDE : Calibration curve is Amplitude

PHASE : Calibration curve is phase

UNDEFINED : Not applicable.

### 2.14 CalDataOrigin

version 1

TOTAL\_POWER

WVR

CHANNEL\_AVERAGE\_AUTO



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 115

CHANNEL\_AVERAGE\_CROSS  
FULL\_RESOLUTION\_AUTO  
FULL\_RESOLUTION\_CROSS  
OPTICAL\_POINTING  
HOLOGRAPHY  
NONE

### 2.15 CalType

version 1 [CalDM.CalData] Used to point to a given CalResult table

CAL\_AMPLI :  
CAL\_ATMOSPHERE :  
CAL\_BANDPASS :  
CAL\_CURVE :  
CAL\_DELAY :  
CAL\_FLUX :  
CAL\_FOCUS :  
CAL\_FOCUS\_MODEL :  
CAL\_GAIN :  
CAL\_HOLOGRAPHY :  
CAL\_PHASE :  
CAL\_POINTING :  
CAL\_POINTING\_MODEL :  
CAL\_POSITION :  
CAL\_PRIMARY\_BEAM :  
CAL\_SEEING :  
CAL\_WVR :

### 2.16 CalibrationDevice

version 1 Devices that may be inserted in the optical path in front of the receiver.

AMBIENT\_LOAD : An absorbing load at the ambient temperature.  
COLD\_LOAD : A cooled absorbing load.  
HOT\_LOAD : A heated absorbing load.  
NOISE\_TUBE\_LOAD : A noise tube.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 116

**QUARTER\_WAVE\_PLATE** : A transparent plate that introduces a 90-degree phase difference between orthogonal polarizations.

**SOLAR\_FILTER** : An optical attenuator (to protect receiver from solar heat).

**NONE** : No device, the receiver looks at the sky (through the telescope).

### 2.17 CalibrationFunction

version 1 Function of a scan in a calibration set. Useful only in real time.

**FIRST** : the scan is the first in a calibration set.

**LAST** : the scan is the last in a calibration set.

**UNSPECIFIED** : the function is not specified.

### 2.18 CalibrationMode

version 1 Modes of calibration

**HOLOGRAPHY** : Holography receiver

**INTERFEROMETRY** : interferometry

**OPTICAL** : Optical telescope

**RADIOMETRY** : total power

**WVR** : water vapour radiometry receiver

### 2.19 CalibrationSet

version 1 Defines sets of calibration scans to be reduced together for a result.

**NONE** : Scan is not part of a calibration set.

**AMPLI\_CURVE** : Amplitude calibration scan (calibration curve to be derived).

**ANTENNA\_POSITIONS** : Antenna positions measurement.

**PHASE\_CURVE** : Phase calibration scan (calibration curve to be derived).

**POINTING\_MODEL** : Pointing calibration scan (pointing model to be derived).

**ACCUMULATE** : Accumulate a scan in a calibration set.

**TEST** : Reserved for development.

**UNSPECIFIED** : Unspecified calibration intent.

### 2.20 CorrelationBit

version 1 [APDM] Number of bits used for correlation

**BITS\_2x2** : two bit correlation

**BITS\_3x3** : three bit correlation

**BITS\_4x4** : four bit correlation



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 117

### 2.21 CorrelationMode

version 1 [ASDM.Binary] Actual data products in binary data

CROSS\_ONLY : Cross-correlations only [not for ALMA]

AUTO\_ONLY : Auto-correlations only

CROSS\_AND\_AUTO : Auto-correlations and Cross-correlations

### 2.22 CorrelatorCalibration

version 1 Internal correlator calibrations performed during this subscan

NONE : No internal correlator calibration

CORRELATOR\_CALIBRATION : Internal correlator calibration.

REAL\_OBSERVATION : A 'real' observation.

### 2.23 CorrelatorName

version 1

ALMA\_ACA

ALMA\_BASELINE

ALMA\_BASELINE\_ATF

ALMA\_BASELINE\_PROTO\_OSF

HERSCHEL

IRAM\_PDB

IRAM\_30M\_VESPA

IRAM\_WILMA

NRAO\_VLA

NRAO\_WIDAR

### 2.24 CorrelatorType

version 1 defines the type of a correlator.

FX : identifies a digital correlator of type FX.

XF : identifies a digital correlator of type XF.

FXF : identifies a correlator of type FXF.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 118

### 2.25 DataContent

version 1 [ASDM.Binaries] Contents of binary data attachment

CROSS\_DATA : Cross-correlation data

AUTO\_DATA : Auto-correlation data

ZERO\_LAGS : Zero-lag data

ACTUAL\_TIMES : Actual times (mid points of integrations)

ACTUAL\_DURATIONS : Actual duration of integrations

WEIGHTS : Weights

FLAGS : Baseband based flags

### 2.26 DataScale

version 1 Data scale (and unit)

K : Visibilities in Antenna temperature scale (in Kelvin)

JY : Visibilities in Flux Density scale (Jy)

CORRELATION : Correlated Power: WIDAR raw output, normalised by DataValid count.

CORRELATION\_COEFFICIENT : Correlation Coefficient (Correlated Power scaled by autocorrelations)

### 2.27 DetectorBandType

version 1 [ASDM.SquareLawDetector] Types of detectors

BASEBAND : Detector in Baseband Processor

DOWN\_CONVERTER : Detector in Down - Converter

HOLOGRAPHY\_RECEIVER : Detector in Holography Receiver

SUBBAND : Detector in subband (tunable digital filter).

### 2.28 DirectionReferenceCode

version 1 defines reference frames to qualify the measure of a direction.

J2000 : mean equator and equinox at J2000.0

JMEAN : mean equator and equinox at frame epoch.

JTRUE : true equator and equinox at frame epoch.

APP : apparent geocentric position.

B1950 : mean epoch and ecliptic at B1950.0.

B1950\_VLA :

BMEAN : mean equator and equinox at frame epoch.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 119

BTRUE : true equator and equinox at frame epoch.  
GALACTIC : galactic coordinates.  
HADEC : topocentric HA and declination.  
AZELSW : topocentric Azimuth and Elevation (N through E).  
AZELSWGEO :  
AZELNE : idem AZEL  
AZELNEGEO :  
JNAT : geocentric natural frame.  
ECLIPTIC : ecliptic for J2000.0 equator, equinox.  
MECLIPTIC : ecliptic for mean equator of date.  
TECLIPTIC : ecliptic for true equator of date.  
SUPERGAL : supergalactic coordinates.  
ITRF : coordinates wrt ITRF earth frame.  
TOPO : apparent topocentric position.  
ICRS :  
MERCURY : from JPL DE table.  
VENUS :  
MARS :  
JUPITER :  
SATURN :  
URANUS :  
NEPTUNE :  
PLUTO :  
SUN :  
MOON :

### 2.29 DopplerReferenceCode

version 1 defines reference frames to qualify the measure of a radial velocity expressed as doppler shift.

RADIO : radio definition :  $1 - F$   
Z : redshift :  $-1 + 1/F$   
RATIO : frequency ratio :  $F$   
BETA : relativistic :  $(1 - F^2)/(1 + F^2)$   
GAMMA :  $(1 + F^2)/(2 * F)$   
OPTICAL :  $ZZ$   
RELATIVISTIC : idem BETA



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 120

### 2.30 DopplerTrackingMode

version 1 Defines the way the Doppler tracking is implemented in the on-line system.

**NONE** No Doppler tracking

**CONTINUOUS** Doppler tracking is continuous (every integration)

**SCAN\_BASED** Doppler tracking only at scan boundaries. This means we update the observing frequency to the correct value, but only at scan boundaries.

**SB\_BASED** Doppler tracking only at the beginning of the SB. We set the frequency at the beginning of the observation but leave it fixed thereafter. For the EVLA this is referred to as "Doppler setting."

### 2.31 FieldCode

version 1 [ASDM.Field] code for Field

**NONE** :

### 2.32 FilterMode

version 1 [APDM.Correlator] Modes of correlator input filtering

**FILTER\_NA** : Not Applicable (2 antenna prototype). The Tunable Filter Banks are not implemented

**FILTER\_TDM** : Time Division Mode. In this mode the Tunable Filter banks are bypassed

**FILTER\_TFB** : The Tunable Filter Bank is implemented and used

**UNDEFINED** : Not defined or not applicable.

### 2.33 FluxCalibrationMethod

version 1 [CalDM.CalFlux] Methods for flux calibration

**ABSOLUTE** : Absolute flux calibration (based on standard antenna)

**RELATIVE** : Relative flux calibration (based on a primary calibrator)

**EFFICIENCY** : Flux calibrator based on tabulated antenna efficiency

### 2.34 FocusMethod

version 1 [CalDM.CalFocus] Method of focus measurement

**THREE\_POINT** : Three-point measurement

**FIVE\_POINT** : Five-point measurement





## 2.35 FrequencyReferenceCode

version 1 defines reference frames to qualify the measure of a frequency.

LABREST : spectral line rest frequency.

LSRD : dynamic local standard of rest.

LSRK : kinematic local standard rest.

BARY : barycentric frequency.

REST : spectral line frequency

GEO : geocentric frequency.

GALACTO : galactocentric frequency.

TOPO : topocentric frequency.

## 2.36 HolographyChannelType

version 1 [ASDM.Holography] Type sof holography receiver output channels

Q2 : Quadrature channel auto-product

QR : Quadrature channel times Reference channel cross-product

QS : Quadrature channel times Signal channel cross-product

R2 : Reference channel auto-product

RS : Reference channel times Signal channel cross-product

S2 : Signal channel auto-product

## 2.37 InvalidatingCondition

version 1 [CalDM.CalReduction] Contitions invalidating result

ANTENNA\_DISCONNECT : Antenna was disconnected

ANTENNA\_MOVE : Antenna was moved

ANTENNA\_POWER\_DOWN : Antenna was powered down

RECEIVER\_EXCHANGE : Receiver was exchanged

RECEIVER\_POWER\_DOWN : Receiver was powered down

## 2.38 NetSideband

version 1 [ASDM.SpectralWindow] Equivalent side band of spectrum frequency axis

NOSB : No side band (no frequency conversion)

LSB : Lower side band

USB : Upper side band

DSB : Double side band



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 122

### 2.39 PointingMethod

version 1 [CalDM.CalPointing] Method of pointing measurement

THREE\_POINT : Three-point scan

FOUR\_POINT : Four-point scan

FIVE\_POINT : Five-point scan

CROSS : Cross scan

CIRCLE : Circular scan

### 2.40 PointingModelMode

version 1 [CalDM.PointingModel] Mode of Pointing Model

RADIO : Radio pointing model

OPTICAL : Optical Pointing Model

### 2.41 PolarizationType

version 1 The polarizations a single receptor can detect

R : Right-handed Circular

L : Left-handed Circular

X : X linear

Y : Y linear

**BOTH** : The receptor responds to both polarizations

### 2.42 PositionMethod

version 1 [CalDM.CalPositions] Method used for measuring antenna positions

DELAY\_FITTING : Delays are measured for each source; the delays are used for fitting antenna position errors.

PHASE\_FITTING : Phases are measured for each source; these phases are used to fit antenna position errors.

### 2.43 PositionReferenceCode

version 1 defines reference frames to qualify the measure of a position.

ITRF : International Terrestrial Reference Frame.

WGS84 : World Geodetic System.

SITE : Site reference coordinate system (ALMA-80.05.00.00-009-B-SPE).

STATION : Antenna station reference coordinate system (ALMA-80.05.00.00-009-SPE).

YOKE : Antenna yoke reference coordinate system (ALMA-980.05.00.00-009-B-SPE)

REFLECTOR : Antenna reflector reference coordinate system (ALMA-80.05.00.00-009-B-SPE).



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 123

### 2.44 PrimitiveDataType

version 1 [ASDM.Binaries] Primitive data types for binary MIME attachments

INT16\_TYPE : 2 bytes signed integer (short).

INT32\_TYPE : 4 bytes signed integer (int).

INT64\_TYPE : 8 bytes signed integer (long long).

FLOAT32\_TYPE : 4 bytes float (float).

FLOAT64\_TYPE : 8 bytes float (double).

### 2.45 ProcessorSubType

version 1 [ASDM.Processor] The tables used to contain device configuration data

ALMA\_CORRELATOR\_MODE : ALMA correlator.

SQUARE\_LAW\_DETECTOR : Square law detector.

HOLOGRAPHY : Holography.

ALMA\_RADIOMETER : ALMA radiometer.

### 2.46 ProcessorType

version 1 [ASDM.Processor] Types of processors

CORRELATOR : A digital correlator

RADIOMETER : A radiometer

SPECTROMETER : An (analogue) multi-channel spectrometer

### 2.47 RadialVelocityReferenceCode

version 1

LSRD

LSRK

GALACTO

BARY

GEO

TOPO



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 124

### 2.48 ReceiverBand

version 1 [ASDM.Receiver] Receiver band names

ALMA\_RB\_01 : ALMA Receiver band 01

ALMA\_RB\_02 : ALMA Receiver band 02

ALMA\_RB\_03 : ALMA Receiver band 03

ALMA\_RB\_04 : ALMA Receiver band 04

ALMA\_RB\_05 : ALMA Receiver band 05

ALMA\_RB\_06 : ALMA Receiver band 06

ALMA\_RB\_07 : ALMA Receiver band 07

ALMA\_RB\_08 : ALMA Receiver band 08

ALMA\_RB\_09 : ALMA Receiver band 09

ALMA\_RB\_10 : ALMA Receiver band 10

ALMA\_RB\_ALL : all ALMA receiver bands.

ALMA\_HOLOGRAPHY\_RECEIVER : Alma transmitter Holography receiver.

BURE\_01 : Plateau de Bure receiver band 1.

BURE\_02 : Plateau de Bure receiver band 2.

BURE\_03 : Plateau de Bure receiver band 3.

BURE\_04 : Plateau de Bure receiver band 4

EVLA\_4 :

EVLA\_P :

EVLA\_L :

EVLA\_C :

EVLA\_S :

EVLA\_X :

EVLA\_Ku :

EVLA\_K :

EVLA\_Ka :

EVLA\_Q :

UNSPECIFIED : receiver band of unspecified origin.



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 125

### 2.49 ReceiverSideband

version 1 [ASDM.SpectralWindow] The type of receiver output a spectral window is fed with

NOSB : direct output signal (no frequency conversion).

DSB : double side band output.

SSB : single side band receiver.

TSB : receiver with dual output.

### 2.50 SBType

version 1 [ASDM.SBSummary] Types of Scheduling Block

OBSERVATORY : Observatory mode scheduling block

OBSERVER : Observer mode scheduling block

EXPERT : Expert mode scheduling block

### 2.51 ScanIntent

version 1 [ASDM.Scan] Scan intents

CALIBRATE\_AMPLI : Amplitude calibration scan

CALIBRATE\_ATMOSPHERE : Atmosphere calibration scan

CALIBRATE\_BANDPASS : Bandpass calibration scan

CALIBRATE\_DELAY : Delay calibration scan

CALIBRATE\_FLUX : flux measurement scan.

CALIBRATE\_FOCUS : Focus calibration scan. Z coordinate to be derived

CALIBRATE\_FOCUS\_X : Focus calibration scan; X focus coordinate to be derived

CALIBRATE\_FOCUS\_Y : Focus calibration scan; Y focus coordinate to be derived

CALIBRATE\_PHASE : Phase calibration scan

CALIBRATE\_POINTING : Pointing calibration scan

CALIBRATE\_POLARIZATION : Polarization calibration scan

CALIBRATE\_SIDEHAND\_RATIO : measure relative gains of sidebands.

CALIBRATE\_WVR : Data from the water vapor radiometers (and correlation data) are used to derive their calibration parameters.

DO\_SKYDIP : Skydip calibration scan

MAP\_ANTENNA\_SURFACE : Holography calibration scan

MAP\_PRIMARY\_BEAM : Data on a celestial calibration source are used to derive a map of the primary beam.

OBSERVE\_TARGET : Target source scan

CALIBRATE\_POL\_LEAKAGE :



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 126

CALIBRATE\_POL\_ANGLE :

TEST : used for development.

UNSPECIFIED : Unspecified scan intent

### 2.52 SchedulerMode

version 1 [ASDM.SBSummary] Scheduler operation mode

DYNAMIC : Dynamic scheduling

INTERACTIVE : Interactive scheduling

MANUAL : Manual scheduling

QUEUED : Queued scheduling

### 2.53 SidebandProcessingMode

version 1 [ASDM.SpectralWindow] Real-time processing to derive sideband data

NONE : No processing

PHASE\_SWITCH\_SEPARATION : Side band separation using 90-degree phase switching

FREQUENCY\_OFFSET\_SEPARATION : Side band separation using offsets of first and second oscillators

PHASE\_SWITCH\_REJECTION : Side band rejection 90-degree phase switching

FREQUENCY\_OFFSET\_REJECTION : Side band rejection using offsets of first and second oscillators

### 2.54 SourceModel

version 1 [CalDM.CalFlux] Source Model

GAUSSIAN : Gaussian source

POINT : Point Source

DISK : Uniform Disk

### 2.55 SpectralResolutionType

version 1 [ASDM.SpectralWindow] The types of spectral resolutions for spectral windows.

CHANNEL\_AVERAGE :

BASEBAND\_WIDE :

FULL\_RESOLUTION :



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 127

### 2.56 StationType

version 1 [ASDM.Station] Type of antenna station

ANTENNA\_PAD : Astronomical Antenna station

MAINTENANCE\_PAD : Maintenance antenna station

WEATHER\_STATION : Weather station

### 2.57 StokesParameter

version 1 Stokes parameters (CASA definition)

I :

Q :

U :

V :

RR :

RL :

LR :

LL :

XX : Linear correlation product

XY :

YX :

YY :

RX : Mixed correlation product

RY : Mixed correlation product

LX : Mixed LX product

LY : Mixed LY correlation product

XR : Mixed XR correlation product

XL : Mixed XL correlation product

YR : Mixed YR correlation product

YL : Mixel YL correlation product

PP :

PQ :

QP :

QQ :

RCIRCULAR :

LCIRCULAR :



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 128

LINEAR : single dish polarization type

PTOTAL : Polarized intensity  $((Q^2 + U^2 + V^2)^{1/2})$  : *LinearlyPolarizedintensity* $((Q^2 + U^2)^{1/2})$

PLINEAR : Polarization Fraction (Ptotal/I)

PFLINEAR : Linear Polarization Fraction (Plinear/I)

PANGLE : Linear Polarization Angle  $(0.5 \arctan(U/Q))$  (in radians)

### 2.58 SubscanIntent

version 1 [ASDM.Subscan] Precise the intent for a subscan

ON\_SOURCE : on-source measurement

OFF\_SOURCE : off-source measurement

MIXED : Pointing measurement, some antennas are on -ource, some off-source

REFERENCE : reference measurement (used for boresight in holography).

SCANNING : antennas are scanning.

HOT : hot load measurement.

AMBIENT : ambient load measurement.

TEST : reserved for development.

UNSPECIFIED : Unspecified

**SIGNAL** : Signal sideband measurement

**IMAGE** : Image sideband measurement

### 2.59 SwitchingMode

version 1 Switching modes: there are two categories of switching modes, those at high rate (chopper wheel, nutator and frequency switch) which involve the BIN axis and those at low rate (frequency, position, load and phase switching) unrelated to the bin axis. Note that in case of frequency switching mode it is the context which tells in which of these two categories it is used.

NO\_SWITCHING : No switching

LOAD\_SWITCHING : Receiver beam is switched between sky and load

POSITION\_SWITCHING : Antenna (main reflector) pointing direction is switched

PHASE\_SWITCHING : 90 degrees phase switching (switching mode used for sideband separation or rejection with DSB receivers)

FREQUENCY\_SWITCHING : LO frequency is switched (definition context sensitive: fast if cycle shorter than the integration duration, slow if e.g. step one step per subscan)

NUTATOR\_SWITCHING : Switching between different directions by nutating the sub-reflector

CHOPPER\_WHEEL : Switching using a chopper wheel





## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 129

### 2.60 SyscalMethod

version 1 [CalDM.CalAtmosphere] Atmosphere calibration methods

TEMPERATURE\_SCALE : Use single direction data to compute  $\tau^*$  scale

SKYDIP : Use a skydip (observing the sky at various elevations) to get atmospheric opacity

SIDEBAND\_RATIO : Measure the sideband gain ratio

### 2.61 TimeSampling

version 1 Time granularity for data

SUBINTEGRATION : Part of an integration

INTEGRATION : Part of a subscan. An integration may be composed of several sub-integrations.

### 2.62 TimeScale

version 1 Time definition

UTC : Universal Time Coordinated

TAI : International Atomic Time (Temps Atomique International)

### 2.63 WeightType

version 1 Type of weighting used.

K : Based on System temperature

JY : Based on Flux (include antenna efficiency)

COUNT\_WEIGHT : Square-root of the number of samples (i.e.  $\sqrt{\text{bandwidth} * \text{time}}$ ) (Are you sure about sqrt?)

### 2.64 WVRMethod

version 1 [CalDM.CalWVR] Methods for WVR Data processing in TelCal

ATM\_MODEL : WVR data reduction uses ATM model

EMPIRICAL : WVR data reduction optimized using actual phase data

### 2.65 WindowFunction

version 1 [APDM; ASDM.ALmaCorrelatorMode] Windowing functions for spectral data apodization

UNIFORM : No windowing

HANNING : Raised cosine:  $0.5 * (1 - \cos(x))$  where  $x = 2 * \pi * i / (N - 1)$



## SDM Tables Short Description

Doc#: COMP-70.75.00.00-00?-A-DSN  
Date: February 24, 2011  
Status: Draft  
Page 130

**HAMMING** : The classic Hamming window is  $W_M(x) = 0.54 - 0.46 * \cos(x)$ . This is generalized to  $W_M(x) = \beta - (1 - \beta) * \cos(x)$  where  $\beta$  can take any value in the range  $[0, 1]$ .  $\beta = 0.5$  corresponds to the Hanning window.

**BARTLETT** : The Bartlett (triangular) window is  $1 - |x/\pi|$ , where  $x = 2 * \pi * i / (N - 1)$ .

**BLACKMANN** : The window function is  $W_B(x) = (0.5 - \beta) - 0.5 * \cos(x_j) + \beta * \cos(2x_j)$ , where  $x_j = 2 * \pi * j / (N - 1)$ . The classic Blackman window is given by  $\beta = 0.08$ .

**BLACKMANN\_HARRIS** : The **BLACKMANN\_HARRIS** window is  $1.0 - 1.36109 * \cos(x) + 0.39381 * \cos(2 * x) - 0.032557 * \cos(3 * x)$ , where  $x = 2 * \pi * i / (N - 1)$ .

**WELCH** : The Welch window (parabolic) is  $1 - (2 * i / N)^2$ .