inhale.base.code.preserve	Preserve old code when new base base release installed Allowed:true or false Default: true
inhale.base.slave.preserve	Preserve code in slave after base release Allowed:false or true Default: false
inhale.sneeze.hosts	hosts on which to inhaled system. Each host can have colon separated list of extensions (_ for no extension) Allowed:valid host name with :ext $: ext..$ Default: none
inhale.sneeze.$< host >$.rcmd	Remote command to start sneeze on host Allowed:rsh or commands like ssh Default: rsh
sneeze.host.aipsext.logfile	name of sneeze log file (replace host.aipsext with your host and aipsext) Allowed:valid file name Default: none
sneeze.host.aipsext.logmail	address to mail the sneeze logfile to (replace host.aipsext with your host and aipsext) Allowed:valid mail address Default: AIPS++inhalenrao.edu
sneeze.base.docs.preserve	Preserve old documentation when new base release installed Allowed:true or false Default: true
sneeze.base.$< arch >$.preserve	Preserve old system when new base release installed Allowed:true or false Default: true

---

1.1.20 account - Tool

Package utility
Module aipsrcdata

AIPS++ account definitions – aipsmgr

Description

The variables in this group have to be defined; they have no defaults. The values are given in the order 'user.group'. They will normally be defined in