extendoptionmenu.done - Function

Package	**display**
Module	**widgets**
Tool	**extendoptionmenu**

Destroy ourselves

Synopsis
done()

Returns
Bool

Description

This tool function destroys the widget.

Example

```
- f := frame();
- m := extendoptionmenu(f, labels="a b c");
- m.done();
T
- m
F
-
```

1.4.11 fontchooserwidget - Tool

Package	**display**
Module	**widgets**

AIPS++widget to help users select a font
g
include "fontchooserwidget.g"

Description

This AIPS++ widget allows the user to select fonts.

fontchooserwidget - Constructor

Package	**display**
Module	**widgets**
Tool	**fontchooserwidget**

Construct a fontchooserwidget

Synopsis

fontchooserwidget(parent, font, widgetset)

Arguments

parent	*Parent of the menu* *Allowed: Tk frame* *Default: F*
font	*Font of text* *Allowed: X font* *Default: F*
widgetset	*Widget set to use* *Allowed: A widgetserver closure tool* *Default: dws*

Returns

fontchooserwidget widget

Description

Constructs a fontchooserwidget according to the specified construction arguments, and returns a subsequence to the widget. Remember to use the `fontchooserwidget` *via the widgetserver if at all possible.*
You may send the fontchooserwidget 3 events

1. **reset** *cause the fontchooser to selected it's initial font.*
2. **map** *causes the fontchooser to become visible if not already.*
3. **unmap** *causes the fontchooser to become invisible if not already.*

The fontchooser widget sends one event