Package utility
Module aipsrcdata

details for the measures data handling – user

Description
The variables in this group describe the non-standard directory lookup for the various tables with e.g. observatories, spectral lines, sources. Default lookup for directories is

```
- ./name
- ./data/name
- $AIPSHOME/data/ephemerides/name ($AIPSHOME is normally ~/aips++)
- $AIPSROOT/data/ephemerides/name ($AIPSROOT is first field of $AIPSPATH)
- $AIPSHOME/data/geodetic/name
- $AIPSROOT/data/geodetic/name
and till at least 1 Jan 2001:
- $AIPSHOME/data/aips/Measures/name
- $AIPSROOT/data/aips/Measures/name
- $AIPSHOME/code/trial/apps/measures
- $AIPSROOT/code/trial/apps/measures
```

Example

```
measures.line.directory:     ~/aips++
```

Use the Lines spectral line table as given in the indicated directory.

Aipsrc Variables

measures.line.directory	directory for the Lines spectral line table Allowed:valid directory Default: see description
measures.observatory.directory	directory for the Observatories table Allowed:valid directory Default: see description
measures.source.directory	directory for the Sources table Allowed:valid directory Default: see description
measures.igrf.directory	directory for the IGRF Earth magnetic field model table Allowed:valid directory Default: see description

1.1.9 measures.comet - Tool